


Fans and drive concepts for rail technology

Product Catalogue 2018-09

ebmpapst

the engineer's choice



Fans and drive concepts for rail technology

Those who have to guarantee maximum reliability every day and want to offer optimum comfort need technologies they can rely on.

To this end, we develop ventilation and drive technology that sets standards - even under consideration of the strictest requirements.



Fans and drive concepts for rail technology

ebmpapst

the engineer's choice



	Page		Page
Information	4	About ebm-papst	4
		ebm-papst: Your highly competent partner in rail engineering	6
		Fire safety in rail vehicles	7
		Product overview	8
		Fans and drive concepts for rail technology	14
		EC / DC centrifugal fans backward-curved Ø 190 - Ø 400	20
		EC / DC axial fans Ø 300 - Ø 500	72
		DC compact fans axial fan Ø 172 x 51, centrifugal fan □ 127 x 25	94
		AC centrifugal fans backward-curved Ø 190 - Ø 280	104
		AC centrifugal fans forward-curved Ø 120 - Ø 250 (with housing, single-intake)	122
		AC centrifugal fans forward-curved Ø 133 - Ø 200 (with housing, dual-intake)	154
		Drive concepts: door drives, drives for entry aids, special applications	178
Accessories	182	FlowGrid air inlet grill	184
		Mounting dimensions for centrifugal modules	185
		Inlet rings for centrifugal fans	186
Technology	190	Connection diagrams	192
		Technical parameters & scope	204
ebm-papst agents	210		210

Information

Fans and drive concepts for rail technology

Accessories

Technology

Agents

About ebm-papst

As technological leader for ventilation and drive engineering, ebm-papst is in demand as an engineering partner in many industries. With over 15,000 different products, we provide the right solution for just about any challenge. Our fans and drives are reliable, quiet and energy-efficient.

Six reasons that make us the ideal partner:

Our systems expertise.

You want the best solution for every project. The interrelationships between ventilation and drive engineering must thus be considered as a whole.

And that's what we do – with motor technology that sets standards, sophisticated electronics and aerodynamic designs – all from a single source and perfectly matched. These system solutions release unique synergies worldwide. And in particular – they relieve you of a lot of work, so that you can concentrate on your core competency.

The ebm-papst spirit of invention.

In addition to our wide range of products, we are always able to develop customized solutions for you. A diversified team of 600 engineers and technicians works at our three locations in Germany: Muldingen, Landshut and St. Georgen. Contact us to discuss your next project.

Our lead in technology.

As pioneer and trail-blazer for developing highly efficient EC technology, we are way ahead of other motor manufacturers. Almost all our products are also available with GreenTech EC technology. The list of benefits is long: higher efficiency, maintenance-free, longer service life, sound reduction, intelligent control characteristics and unrivalled energy efficiency with savings of up to 80 % compared to conventional AC technology. Let our technology be your competitive advantage as you lead in your industry.

Closeness to our customers.

ebm-papst has 25 production locations worldwide (including facilities in Germany, China and the USA), together with 49 sales offices, each of which has a dense network of sales representatives. You will always have a local contact, someone who speaks your language and knows your market.

Our standard of quality.

Of course you can rely on the highest standards of quality with our products. Our quality management is uncompromising, at every step in every process. This is underscored by our certification according to international standards including DIN EN ISO 9001, TS declaration of conformity and DIN EN ISO 14001.

Our sustainable approach.

Assuming responsibility for the environment, for our employees and for society is an integral part of our corporate philosophy. We develop products with an eye to maximum environmental compatibility, in particular resource-preserving production methods. We promote environmental awareness among our young staff and are actively involved in sports, culture and education. That's what makes us a leading company – and an ideal partner for you.

The story of our success to *market and technology pioneer.*

- 1963 Founding of **Elektrobau Mulfingen GmbH & Co. KG** by Gerhard Sturm and Heinz Ziehl.
- 1965 First tubeaxial fan developed in EC/DC technology.
- 1966 ebm's success takes off with the new 68 motor.
- 1972 The first ebm foreign subsidiary is established in Sweden.
- 1988 Gerhard Sturm is awarded the Federal Cross of Merit.
- 1990 The sixty-millionth external-rotor fan is produced.
- 1992 Acquisition of **PAPST Motoren GmbH** in St. Georgen.
- 1997 Buyout of the **Landshut** (mvl) plant.
- 1998 Development of first fans with integrated electronics.
- 2003 Change of name to **ebm-papst**.
- 2008 The **HyBlade**® range of fans sets new efficiency standards.
- 2010 **GreenTech** – our sign for energy efficiency and resource preservation.
- 2011 **RadiCal** defines a new standard for EC centrifugal fans.
- 2013 ebm-papst takes over the gearbox specialist Zeitlauf and wins the **German Sustainability Award**.
- 2014 Team partnership with Mercedes AMG PETRONAS Formula 1 team.
- 2015 **RadiPac** pushes the limits of efficiency.
- 2016 **AxiBlade** sets new standards in ventilation, refrigeration and air-conditioning.



ebm-papst: Your highly competent partner in *rail engineering*

Creating the ideal fan solution.

The area of railways places particular requirements on a product. Fans developed uniquely for rail technology and for the specific field of application will help to achieve a high level of customer satisfaction in the long-term. Introducing standard products in rail vehicles is frivolous and sooner or later becomes expensive for the customer. To find the best solution for the individual rail use in each case, a comparison of the requirements in the field and the performance features of the fan is necessary.

• **EN 50155: 2007/2017 Railway applications. Electronic equipment used on rolling stock / rail technology fans by ebm-papst are compliant with EN 50155.**

- **IEC 61373: 2010 Shock and vibration tests**

The fans are tested according to category 1B. The entire system must be tested separately.

- **EN 60721-3-5: 1998 Environmental conditions**

Climatic environmental conditions: 5K2

Chemically active substances: 5C1

Mechanically active substances: 5S1

Biological environmental conditions: 5B1

Contamination agents: 5F1

Mechanical environmental conditions: 5M1

Environmental conditions tested according to EN 50155

Section 13.3, table 12

- **EN 50121-3-2: 2016 Electromagnetic compatibility**

- **EN 50124-1: 2017 Insulation coordination**

Note on routine testing of customer units with 24 VDC fans:
Before insulation testing, all fan connections must be disconnected from the customer unit.

• **EN 15085-1/3: 2013 Welding of railway vehicles and components / weld seam quality CPC3**

• **EN 45545-2+A1: 2015 Fire protection on railway vehicles**
The fans fulfil the requirements according to HL3. The fire protection requirements of the entire system must be assessed separately.

• **EN 50533/A1: 2016 Properties of 3-phase electrical system voltage / Class 1 electrical system architecture is a prerequisite for using EC fans.**

Our advantage lies in the perfect interaction.

Significantly increased passenger and cargo demands due to advancing globalization require new solutions, particularly in rail traffic. Powerful and reliable vehicle concepts provide the basis for vehicles for transport solutions that are more efficient and, above all, more environmentally friendly. An essential part of this effort is cooling both diesel-powered and electrically powered rail cars as well as providing maximum comfort for passenger transportation. Precisely in this area, ebm-papst has time and again set new standards with brushless fans.

Leading technologies, groundbreaking application solutions, innovative products – all of these would not be possible if we did not see the big picture:

Aerodynamic optimization and therefore the perfect combination of motor technology, electronics and aerodynamics. Our three core competencies are in direct relationship to each other in our products. The objective is always to use air and motion as efficiently as possible, whether in the tightest spaces, in large dimensions or under extreme ambient conditions. We believe that this cohesive strategy is the only way to give our customers high quality and perfectly optimized end products. Whether they are high-performance driver's cab climate control systems and heating units, versatile passenger compartment systems or effective cooling of power electronics in locomotives.

In order to achieve an aerodynamically optimum shape for our fans, we design fan blades, impellers and ducted housings to match the relevant application environment. From seemingly small details, such as the bladetip slip with winglets, result significant optimizations for noise reduction with even higher efficiencies. And when they are combined with intelligent electronics, the drive engineering and aero dynamics then operate as a system solution optimally matched to each other. The perfect combination thus arises: our lead in global competition.

If the conditions under application exceed the tested requirements, then please arrange a consultation with ebm-papst.

Fire safety in rail vehicles

The European standard EN 45545 for fire safety in rail vehicles was ratified in 2013, and the transitional period for national sets of rules expired at the end of March 2016.

The seven-part standard has the objective of protecting passengers and staff in case of fire on board and assuring evacuation. Part 2 of the standard describes the requirements for the degree of flammability of materials and components.

The level of severity of the limit values to be adhered to depends on the hazard level. There are three hazard levels (HL). HL1 is the lowest level and HL3 designates the strictest limit values.

The operating and construction classes of the respective components determine the component's hazard level.

With its series for railway applications, ebm-papst offers fans that are precisely tailored to comply with the fire safety criteria.

Compliance with the requirements of the standards is proven with material tests and extensive product assessment, as well as with independent appraisals.

The findings confirm that the design and material selection completely satisfy the requirements of DIN EN 45545-2 and meet the requirements for HL3.

Concretely, this means that all the relevant components possess the test certificates they require and that they are all currently valid.

Specific properties of the products' construction were also verified.

ebm-papst subjected the products to voluntary testing and certification by TÜV SÜD.

The test certificates granted confirm that the ebm-papst fans presented in this catalog an intended for railway applications meet all the relevant safety requirements and possess the relevant product properties required.


The certification also includes regular production facilities monitoring.





The fire safety substantiation confirms the fans' unlimited suitability for use in rail vehicles.


Product overview – Fans and drive concepts for rail technology



EC / DC dual centrifugal fans (forward curved with housing)



Ø	Nominal voltage	Air performance	Dual centrifugal fan forward curved with housing 	on Page
097	24 V DC	1310	K3G097AS8181	16
	24 V DC	1580	K3G097AS8282	
	110 V DC	1180	K3G097AT85P1	

EC / DC centrifugal fans (backward curved)

Ø	Nominal voltage	Air performance	Centrifugal fan backward curved 	With support structure 	on Page
190	24 V DC	750	R1G190RD7981	---	22
	110 V DC	930	R3G190RY85P1	---	
220	24 V DC	1080	R1G220RD1081	---	26
	110 V DC	1280	R3G220RY90P1	---	
250	24 V DC	1260	R1G250RC8781	---	30
	24 V DC	2100	R3G250RU2781	K3G250RU2781	
	110 V DC	1600	R3G250RY90P1	---	
	110 V DC	2050	R3G250RR09P1	K3G250RR09P1	
	400 V AC	2120	R3G250RR04N1	K3G250RR04N1	
250 (Alu)	110 V DC	3150	R3G250BB09S1	K3G250BB09S1	38
	400 V AC	3500	R3G250BB01N1	K3G250BB01N1	
280	24 V DC	2000	R1G280RC7181	---	42
	24 V DC	2750	R3G280RU2681	K3G280RU2681	
	24 V DC	3300	R3G280RU6582	K3G280RU6582	
	110 V DC	3280	R3G280RR10P1	K3G280RR10P1	
	400 V AC	3320	R3G280RR05N1	K3G280RR05N1	
280 (Alu)	110 V DC	3480	R3G280BD13S1	K3G280BD13S1	50
	400 V AC	3800	R3G280BC01N1	K3G280BC01N1	
310	24 V DC	3750	R3G310RU2981	K3G310RU2981	54
	110 V DC	3500	R3G310RR12P1	K3G310RR12P1	
	400 V AC	3800	R3G310RR05N1	K3G310RR05N1	
310 (Alu)	110 V DC	4950	R3G310BE84S1	K3G310BE84S1	60
	400 V AC	5200	R3G310BE90N1	K3G310BE90N1	
355	110 V DC	4600	R3G355RS13P1	---	64
	110 V DC	5500	R3G355RJ85S1	---	
	400 V AC	5550	R3G355RJ76N1	---	
400 (Alu)	400 V AC	9200	R3G400BE08N1	---	68


EC / DC axial fans					
Ø	Nominal voltage	Air performance	Axial fan		on Page
300 / 385	24 V DC	2650		W3G300BV2582	74
	24 V DC	4100		W3G385CT6581	
300 / 350	110 V DC	3100		W3G300CT80P1	78
	110 V DC	3350		W3G350CT81P1	

EC / DC axial fans						
Ø	Nominal voltage	Air performance	Axial fan		With round full nozzle 	on Page
400	110 V DC	5850	A3G400BK13P3		W3G400CK13P3	82
450	110 V DC	7550	A3G450BL17P3		W3G450CL17P3	86
	400 V AC	7250	A3G450BL12N1		W3G450CL12N1	
500	110 V DC	10500	A3G500BA73S1		W3G500CA73S1	90
	400 V AC	10500	A3G500BA74N1		W3G500CA74N1	

DC compact fans						
	Nominal voltage	Air performance	Axial fan		Radial fan 	on Page
6300 NTD	24 V DC	820	6314N2TDHOU-305		---	96
RLF 100	24 V DC	65	---		RLF100-11/14PU-217	100


Subject to technical changes.

Product overview – Fans and drive concepts for *rail technology*


AC centrifugal fans (<i>backward curved</i>)				
Ø	Nominal voltage	Air performance	Centrifugal fan backward curved 	on Page
190	400 V AC / Y / 50 Hz	550	R2D190RB1811	106
	400 V AC / Y / 60 Hz	600		
220	400 V AC / Δ / 50 Hz	1000	R2D220RC3611	110
	400 V AC / Y / 50 Hz	900		
	480 V AC / Δ / 60 Hz	1200		
	480 V AC / Y / 60 Hz	1000		
250	400 V AC / Δ / 50 Hz	1400	R2D250RC1011	114
	400 V AC / Y / 50 Hz	1180		
	480 V AC / Δ / 60 Hz	1680		
	480 V AC / Y / 60 Hz	1380		
280	400 V AC / Δ / 50 Hz	3000	R2D280RB0811	118
	400 V AC / Y / 50 Hz	2250		

Subject to technical changes.


AC centrifugal fans (forward curved with housing)

Ø	Nominal voltage	Air performance	Centrifugal fan forward curved with housing single-intake 	on Page
120	400 V AC / Y / 50 Hz	290	G2D120AA2203	124
	480 V AC / Y / 60 Hz	250		
140	400 V AC / Δ / 50 Hz	460	G2D140AC3803	128
	400 V AC / Y / 50 Hz	320		
	480 V AC / Δ / 60 Hz	530		
	480 V AC / Y / 60 Hz	350		
160	400 V AC / Δ / 50 Hz	670	G2D160AF1203	132
	400 V AC / Y / 50 Hz	410		
	400 V AC / Δ / 60 Hz	500		
	400 V AC / Y / 60 Hz	310		
180	400 V AC / Δ / 50 Hz	460	G2D180AB1003	136
	400 V AC / Y / 50 Hz	320		
	480 V AC / Δ / 60 Hz	530		
	480 V AC / Y / 60 Hz	350		
180	400 V AC / Δ / 50 Hz	1010	G4D180FF2402	140
	400 V AC / Y / 50 Hz	750		
	480 V AC / Δ / 60 Hz	1180		
	480 V AC / Y / 60 Hz	800		
200	400 V AC / Δ / 50 Hz	1400	G4D200BL1903	144
	400 V AC / Y / 50 Hz	1000		
	480 V AC / Δ / 60 Hz	1180		
	480 V AC / Y / 60 Hz	880		
225	400 V AC / Δ / 50 Hz	1600	G4D225FK2002	148
	400 V AC / Y / 50 Hz	1220		
	480 V AC / Δ / 60 Hz	1700		
	480 V AC / Y / 60 Hz	1280		
250	400 V AC / Δ / 50 Hz	1980	G4D250DC1402	152
	400 V AC / Y / 50 Hz	1580		
	480 V AC / Δ / 60 Hz	2000		
	480 V AC / Y / 60 Hz	1560		

Product overview – Fans and drive concepts for rail technology

AC centrifugal fans (forward curved with housing)					
Ø	Nominal voltage	Air performance	Centrifugal fan forward curved with housing dual-intake		on Page
133	400 V AC / Δ / 50 Hz	740	D2D133DB4003		158
	400 V AC / Y / 50 Hz	480			
	400 V AC / Δ / 60 Hz	690			
	400 V AC / Y / 60 Hz	420			
146	400 V AC / Δ / 50 Hz	800	D2D146AA1203		162
	400 V AC / Y / 50 Hz	520			
	400 V AC / Δ / 60 Hz	640			
	400 V AC / Y / 60 Hz	380			
160	400 V AC / Y / 50 Hz	1520	D2D160BE0203		166
	400 V AC / Y / 60 Hz	1700			
180	400 V AC / Y / 50 Hz	1780	D4D180BB0903		170
	480 V AC / Y / 60 Hz	1760			
200	400 V AC / Y / 50 Hz	2480	D4D200BA0103		174
	480 V AC / Y / 60 Hz	2300			

Subject to technical changes.



EC / DC dual centrifugal fans *forward curved with housing* Ø 097

ebmpapst

the engineer's choice

	Page
Ø 097	16

EC / DC dual centrifugal fans

forward curved with housing, $\varnothing 097$ mm



Material/surface

- Scroll housing: PA66 plastic, black
- Impeller: PA66 plastic, black


Mechanical data

- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 18	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements
 Air performance measured according to: ISO 5801, installation category A, with ebm-papst scroll housing without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L _{WA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)			°C			
Voltage range 16-32 V DC												
A	1	24	3900	435	16,6	84	I	Any	-40..+70	Motor: IP 24 KM Electr.: IP 66/69 K	B	BA3)
	2	24	4375	412	15,8	82						
	3	24	4620	324	12,5	80						
	4	24	4820	233	9,0	79						
B	1	24	4680	740	28,0	88	I	Any	-40..+70	Motor: IP 24 KM Electr.: IP 66/69 K	B	BA2)
	2	24	5025	740	28,0	87						
	3	24	5380	659	25,3	85						
	4	24	5500	441	16,9	84						
Voltage range 77-138 V DC												
C	1	110	3450	330	3,0	81	III	Any	-40..+60	IP 6K9K	B	BA5)
	2	110	4375	330	3,0	80						
	3	110	5350	330	3,0	82						
	4	110	5495	253	2,3	82						

Values set in blue are nominal data at operating point with maximum load.



Subject to change

Curve	Dual centrifugal fan	
	Part number	Weight
A	K3G097AS8181	2,00
B	K3G097AS8282	2,00
C	K3G097AT85P1	2,65



A K3G097AS8181 (Dual centrifugal fan)

Dimensions in mm





Cable (halogen-free):

- ① BETAtrans® GKW R 2.5 mm², 2x crimped ferrules (brown, black)
- ② BETAtrans® GKW R 1.0 mm², 4x crimped ferrules (yellow, orange, blue, white)

Pin assignment: see connection diagram

B K3G097AS8282 (Dual centrifugal fan)

Dimensions in mm




Cable (halogen-free):

- ① BETAtrans® 3 GKW 6.0 mm², 2x crimped ferrules (brown, black)
- ② BETAtrans® 3 GKW 1.0 mm², 2x crimped ferrules (yellow, white)

Pin assignment: see connection diagram

C K3G097AT85P1 (Dual centrifugal fan)

Dimensions in mm



Cable (halogen-free):

- ① BETrans[®] GKW Flex R, 10G 1.0 mm², 10x crimped splices

Pin assignment: see connection diagram



EC / DC centrifugal fans *backward curved* Ø 190 - Ø 400

ebmpapst

the engineer's choice

	Page
Ø 190 RadiCal	22
Ø 220 RadiCal	26
Ø 250 RadiCal	30
Ø 250 Aluminium impeller	38
Ø 280 RadiCal	42
Ø 280 Aluminium impeller	50
Ø 310 RadiCal	54
Ø 310 Aluminium impeller	60
Ø 355 RadiCal	64
Ø 400 Aluminium impeller	68

EC / DC centrifugal fans

backward curved, $\varnothing 190$ mm



Material/surface

- Impeller: PA66 plastic, black
- Rotor: Painted black/galvanized
- Electronics housing: Die-cast aluminium


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 24	Drawings
on Page 182	Accessories
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com




Measuring requirements


Air performance measured according to: ISO 5801, installation category A, with ebm-papst inlet ring without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P _{ed}	Max. Input current I	Sound power level L _{WA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)			°C			
Voltage range 16-32 V DC												
A	①	24	4200	135	5,60	81	III	Shaft horizontal or rotor on bottom	-25..+60	Motor: IP 24 KM Electr.: IP 66/69 K	B	BA1)
	②	24	4080	142	5,90	77						
	③	24	3985	147	6,12	73						
	④	24	4115	140	5,83	75						
Voltage range 77-138 V DC												
B	①	110	5420	270	2,50	88	I	Any	-40..+60	IP 6K9K	B	BA5)
	②	110	5165	270	2,50	84						
	③	110	5000	270	2,50	80						
	④	110	5160	270	2,50	81						

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan	
	Part number	Weight
		kg
A	R1G190RD7981	1,45
B	R3G190RY85P1	2,00




- ① **Accessory part:** Inlet ring 09576-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 6 mm
- ③ **Cable:** 4x BETAtrans[®] GKW R 0.75 mm², 4x crimped splices

Pin assignment: see connection diagram

B R3G190RY85P1 (Centrifugal fan)

Dimensions in mm



- ① **Accessory part:** Inlet ring 09576-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 10 mm
- ③ **Max. clearance of screw:** max. 8 mm
- ④ **Cable (halogen-free):** BETAtrans[®] GKW Flex R, 10G 1.0 mm², 10x crimped splices

Pin assignment: see connection diagram

EC / DC centrifugal fans

backward curved, $\varnothing 220$ mm



Material/surface

- Impeller: PA66 plastic, black
- Rotor: Painted black/galvanized
- Electronics housing: Die-cast aluminium


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 28	Drawings
on Page 182	Accessories
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com




Measuring requirements


Air performance measured according to: ISO 5801, installation category A, with ebm-papst inlet ring without contact protection.
Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L _{WA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)			°C			
Voltage range 16-32 V DC												
A	1	24	3050	125	5,20	78	III	Shaft horizontal or rotor on bottom	-25..+60	Motor: IP 24 KM Electr.: IP 66/69 K	B	BA1)
	2	24	3085	131	5,43	75						
	3	24	2965	132	5,50	71						
	4	24	3065	130	5,40	72						
Voltage range 77-138 V DC												
B	1	110	4125	265	2,40	87	I	Any	-40..+60	IP 6K9K	B	BA5)
	2	110	4050	265	2,50	83						
	3	110	3850	265	2,50	78						
	4	110	4045	265	2,50	81						

Values set in blue are nominal data at operating point with maximum load.


Subject to change

Curve		
	Centrifugal fan	
	Part number	Weight
		kg
A	R1G220RD1081	1,50
B	R3G220RY90P1	2,10



- ① **Accessory part:** Inlet ring 09609-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 6 mm
- ③ **Cable:** 4x BETAtrans[®] GW R 0.75 mm², 4x crimped splices

Pin assignment: see connection diagram



- ① Accessory part: Inlet ring 09609-2-4013, not included in scope of delivery

Dimensions: see "Accessories" chapter

- ② Max. clearance of screw: max. 10 mm
 ③ Max. clearance of screw: max. 8 mm
 ④ Cable (halogen-free): BETAtrans[®] GWK Flex R, 10G 1.0 mm², 10x crimped splices

Pin assignment: see connection diagram

EC / DC centrifugal fans

backward curved, $\varnothing 250$ mm



Material/surface

- Impeller: PA66 plastic, black
- Rotor: Painted black/galvanized
- Electronics housing: Die-cast aluminium
- Support structure: Aluminium
- Inlet ring: Sheet steel, galvanized


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 32	Drawings
on Page 182	Accessories
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com




Measuring requirements
 Air performance measured according to: ISO 5801, installation category A, with ebm-papst inlet ring without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P _{ed}	Max. Input current I	Sound power level L _{WA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)			°C			
Voltage range 16-32 V DC												
A	1	24	2500	120	4,90	75	III	Shaft horizontal or rotor on bottom	-25..+60	Motor: IP 24 KM Electr.: IP 66/69 K	B	BA1)
	2	24	2420	123	5,14	73						
	3	24	2350	130	5,39	69						
	4	24	2420	124	5,16	71						
B	1	24	3860	410	15,8	87	III	Any	-40..+70	Motor: IP 24 KM Electr.: IP 66/69 K	B	BA4)
	2	24	3860	513	19,8	85						
	3	24	3860	568	21,9	81						
	4	24	3860	560	21,6	82						
Voltage range 77-138 V DC												
C	1	110	3195	250	2,30	84	I	Any	-40..+60	IP 6K9K	B	BA5)
	2	110	3045	250	2,30	79						
	3	110	2950	250	2,30	73						
	4	110	3130	250	2,30	78						
D	1	110	3860	447	4,06	86	I	Shaft horizontal or rotor on bottom	-40..+60	IP 55 acc. to EN 60529	F	BA6)
	2	110	3815	510	4,64	83						
	3	110	3800	540	4,90	80						
	4	110	3840	510	4,63	82						
Nominal voltage range 380-480 V AC												
E	1	400	4000	476	0,78	87	I	Shaft horizontal or rotor on bottom	-40..+70	IP 55 acc. to EN 60529	F	BA7)
	2	400	4000	560	0,92	84						
	3	400	4000	595	0,95	82						
	4	400	4000	537	0,87	86						

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve	Centrifugal fan		with support structure	
	Part number	Weight kg	Part number	Weight kg
A	R1G250RC8781	2,00	-----	-----
B	R3G250RU2781	2,80	K3G250RU2781	8,70
C	R3G250RY90P1	2,30	-----	-----
D	R3G250RR09P1	4,10	K3G250RR09P1	9,20
E	R3G250RR04N1	4,60	K3G250RR04N1	11,70




- ① **Accessory part:** Inlet ring 96359-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 6 mm
- ③ **Cable:** 4x BETAtrans[®] GKW R 0.75 mm², 4x crimped splices

Pin assignment: see connection diagram


B R3G250RU2781 (Centrifugal fan)

Dimensions in mm



B K3G250RU2781 (Centrifugal fan with support structure)


Dimensions in mm



- ① **Accessory part:** Inlet ring 96359-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 12 mm, tapping hole ready for self-tapping M6 screw
- ③ **Max. clearance of screw:** max. 10 mm, tapping hole ready for self-tapping M5 screw
- ④ **Max. clearance of screw:** max. 8 mm, tapping hole ready for self-tapping M4 screw
- ⑤ **Cable (halogen-free):** 2x BETAtrans[®] GKW R 2.5 mm², 2x crimped ferrules
2x BETAtrans[®] GKW R 1.0 mm², 2x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter




- ① Accessory part: Inlet ring 96359-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② Max. clearance of screw: max. 10 mm
- ③ Max. clearance of screw: max. 8 mm
- ④ Cable (halogen-free): BETAtrans[®] GKW Flex R, 10G 1.0 mm², 10x crimped splices

Pin assignment: see connection diagram


D R3G250RR09P1 (Centrifugal fan)

Dimensions in mm



D K3G250RR09P1 (Centrifugal fan with support structure)

Dimensions in mm




- ① **Accessory part:** Inlet ring 96359-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 16 mm
- ③ **Cable (halogen-free):** 3x BETAtrans[®] 3 GW flex, 4G 1.5 mm², 3x crimped ferrules
- ④ **Cable (halogen-free):** 7x BETAtrans[®] 3 GW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter


E R3G250RR04N1 (Centrifugal fan)

Dimensions in mm



E K3G250RR04N1 (Centrifugal fan with support structure)

Dimensions in mm



- ① **Accessory part:** Inlet ring 96359-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 16 mm
- ③ **Cable (halogen-free):** 4x BETAtrans[®] 3 GW flex, 4G 1.5 mm², 4x crimped ferrules
- ④ **Cable (halogen-free):** 7x BETAtrans[®] 3 GW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter

EC / DC centrifugal fans

backward curved, Ø 250 mm, Aluminium impeller



Material/surface

- Impeller: Sheet aluminium
- Rotor: Painted black
- Electronics housing: Die-cast aluminium
- Support structure: Aluminium
- Inlet ring: Sheet steel, galvanized


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 40	Drawings
on Page 182	Accessories
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements

Air performance measured according to: ISO 5801, installation category A, with ebm-papst inlet ring without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P _{ed}	Max. Input current I	Sound power level L _{WA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)			°C			
Voltage range 77-138 V DC												
A	1	110	3695	671	6,10	85	I	Shaft horizontal or rotor on bottom	-40..+60	IP 55 acc. to EN 60529	F	BA6)
	2	110	3635	765	6,95	81						
	3	110	3600	800	7,30	79						
	4	110	3660	759	6,90	86						
Nominal voltage range 380-480 V AC												
B	1	400	4000	781	1,26	87	I	Shaft horizontal or rotor on bottom	-40..+60	IP 55 acc. to EN 60529	F	BA7)
	2	400	4000	981	1,55	82						
	3	400	4000	1050	1,60	81						
	4	400	4000	953	1,52	89						


Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve	Centrifugal fan		with support structure	
	Part number	Weight kg	Part number	Weight kg
A	R3G250BB09S1	5,10	K3G250BB09S1	11,30
B	R3G250BB01N1	5,10	K3G250BB01N1	11,30


A R3G250BB09S1 (Centrifugal fan)

Dimensions in mm



A K3G250BB09S1 (Centrifugal fan with support structure)

Dimensions in mm




- ① **Accessory part:** Inlet ring 25070-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 16 mm
- ③ **Cable (halogen-free):** 3x BETAtrans[®] 3 GW flex, 4G 1.5 mm², 3x crimped ferrules
- ④ **Cable (halogen-free):** 7x BETAtrans[®] 3 GW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter


B R3G250BB01N1 (Centrifugal fan)

Dimensions in mm



B K3G250BB01N1 (Centrifugal fan with support structure)

Dimensions in mm



- ① **Accessory part:** Inlet ring 25070-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 16 mm
- ③ **Cable (halogen-free):** 4x BETAtrans[®] 3 GW flex, 4G 1.5 mm², 4x crimped ferrules
- ④ **Cable (halogen-free):** 7x BETAtrans[®] 3 GW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter

EC / DC centrifugal fans

backward curved, $\varnothing 280$ mm



Material/surface

- Impeller: PA66 plastic, black
- Rotor: Painted black
- Electronics housing: Die-cast aluminium
- Support structure: Aluminium
- Inlet ring: Sheet steel, galvanized


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 44	Drawings
on Page 182	Accessories
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com




Measuring requirements


Air performance measured according to: ISO 5801, installation category A, with ebm-papst inlet ring without contact protection. Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P _{ed}	Max. Input current I	Sound power level L _{WA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC										
Voltage range 16-32 V DC												
A	1	24	1700	105	4,40	70	III	Any	-25..+60	Motor: IP 24 KM Electr.: IP 66/69 K	B	BA1)
	2	24	1595	111	4,60	65						
	3	24	1550	112	4,68	60						
	4	24	1635	109	4,52	65						
B	1	24	2350	252	10,5	80	III	Any	-40..+70	Motor: IP 24 KM Electr.: IP 66/69 K	B	BA3)
	2	24	2280	298	12,4	75						
	3	24	2265	304	12,6	73						
	4	24	2305	280	11,7	74						
C	1	24	2830	460	18,0	85	III	Shaft horizontal or rotor on bottom	-40..+70	Motor: IP 24 KM Electr.: IP 66/69 K	B	BA4)
	2	24	2810	584	22,4	81						
	3	24	2810	645	24,8	77						
	4	24	2835	623	23,9	77						
Voltage range 77-138 V DC												
D	1	110	2810	436	4,00	84	I	Shaft horizontal or rotor on bottom	-40..+60	IP 55 acc. to EN 60529	F	BA6)
	2	110	2715	495	4,50	77						
	3	110	2635	495	4,50	73						
	4	110	2760	491	4,50	75						
Nominal voltage range 380-480 V AC												
E	1	400	2900	473	0,81	86	I	Shaft horizontal or rotor on bottom	-40..+60	IP 55 acc. to EN 60529	F	BA7)
	2	400	2900	599	1,01	80						
	3	400	2900	640	1,05	76						
	4	400	2900	587	0,97	77						

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve				
	Centrifugal fan		with support structure	
	Part number	Weight	Part number	Weight
		kg		kg
A	R1G280RC7181	2,30	-----	-----
B	R3G280RU2681	3,00	K3G280RU2681	9,20
C	R3G280RU6582	3,00	K3G280RU6582	9,20
D	R3G280RR10P1	4,20	K3G280RR10P1	9,60
E	R3G280RR05N1	4,90	K3G280RR05N1	11,70




- ① **Accessory part:** Inlet ring 28000-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 6 mm
- ③ **Cable:** 4x BETAtrans[®] GWK R 0.75 mm², 4x crimped splices

Pin assignment: see connection diagram


B R3G280RU2681 (Centrifugal fan)

Dimensions in mm



B K3G280RU2681 (Centrifugal fan with support structure)

Dimensions in mm




- ① **Accessory part:** Inlet ring 28000-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 12 mm, tapping hole ready for self-tapping M6 screw
- ③ **Max. clearance of screw:** max. 10 mm, tapping hole ready for self-tapping M5 screw
- ④ **Max. clearance of screw:** max. 8 mm, tapping hole ready for self-tapping M4 screw
- ⑤ **Cable (halogen-free):** 2x BETAtrans® GKW R 2.5 mm², 2x crimped ferrules
4x BETAtrans® GKW R 1.0 mm², 4x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter


C R3G280RU6582 (Centrifugal fan)

Dimensions in mm



C K3G280RU6582 (Centrifugal fan with support structure)

Dimensions in mm




- ① **Accessory part:** Inlet ring 28000-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 12 mm, tapping hole ready for self-tapping M6 screw
- ③ **Max. clearance of screw:** max. 10 mm, tapping hole ready for self-tapping M5 screw
- ④ **Max. clearance of screw:** max. 8 mm, tapping hole ready for self-tapping M4 screw
- ⑤ **Cable (halogen-free):** 2x BETAtrans® GKW R 2.5 mm², 2x crimped ferrules
2x BETAtrans® GKW R 1.0 mm², 2x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter


D R3G280RR10P1 (Centrifugal fan)

Dimensions in mm



D K3G280RR10P1 (Centrifugal fan with support structure)

Dimensions in mm




- ① **Accessory part:** Inlet ring 28000-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 16 mm
- ③ **Cable (halogen-free):** 3x BETAtrans[®] 3 GKW flex, 4G 1.5 mm², 3x crimped ferrules
- ④ **Cable (halogen-free):** 7x BETAtrans[®] 3 GKW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter


E R3G280RR05N1 (Centrifugal fan)

Dimensions in mm



E K3G280RR05N1 (Centrifugal fan with support structure)

Dimensions in mm



- ① **Accessory part:** Inlet ring 28000-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 16 mm
- ③ **Cable (halogen-free):** 4x BETAtrans[®] 3 GW flex, 4G 1.5 mm², 4x crimped ferrules
- ④ **Cable (halogen-free):** 7x BETAtrans[®] 3 GW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter

EC / DC centrifugal fans

backward curved, Ø 280 mm, Aluminium impeller



Material/surface

- Impeller: Sheet aluminium
- Rotor: Painted black
- Electronics housing: Die-cast aluminium
- Support structure: Aluminium
- Inlet ring: Sheet steel, galvanized


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 52	Drawings
on Page 182	Accessories
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements

Air performance measured according to: ISO 5801, installation category A, with ebm-papst inlet ring without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_p measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L_{wA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)			°C			
Voltage range 77-138 V DC												
A	1	110	3140	743	6,80	88	I	Shaft horizontal or rotor on bottom	-40..+60	IP 55 acc. to EN 60529	F	BA6)
	2	110	3120	882	8,00	85						
	3	110	3100	920	8,40	82						
	4	110	3140	861	7,80	82						
Nominal voltage range 380-480 V AC												
B	1	400	3140	743	1,21	87	I	Shaft horizontal or rotor on bottom	-40..+60	IP 55 acc. to EN 60529	F	BA7)
	2	400	3140	922	1,47	83						
	3	400	3140	975	1,50	80						
	4	400	3140	931	1,48	82						


Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve	Centrifugal fan		with support structure	
	Part number	Weight kg	Part number	Weight kg
A	R3G280BD13S1	8,00	K3G280BD13S1	14,40
B	R3G280BC01N1	6,90	K3G280BC01N1	13,30


A R3G280BD13S1 (Centrifugal fan)

Dimensions in mm



A K3G280BD13S1 (Centrifugal fan with support structure)

Dimensions in mm




- ① **Accessory part:** Inlet ring 28070-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 16 mm
- ③ **Cable (halogen-free):** 3x BETAtans[®] 3 GW flex, 4G 1.5 mm², 3x crimped ferrules
- ④ **Cable (halogen-free):** 7x BETAtans[®] 3 GW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter


B R3G280BC01N1 (Centrifugal fan)

Dimensions in mm



B K3G280BC01N1 (Centrifugal fan with support structure)

Dimensions in mm



- ① **Accessory part:** Inlet ring 28070-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 16 mm
- ③ **Cable (halogen-free):** 4x BETAtrans[®] 3 GW flex, 4G 1.5 mm², 4x crimped ferrules
- ④ **Cable (halogen-free):** 7x BETAtrans[®] 3 GW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter

EC / DC centrifugal fans

backward curved, $\varnothing 310$ mm



Material/surface

- Impeller: PA66 plastic, black
- Rotor: Painted black
- Electronics housing: Die-cast aluminium
- Support structure: Aluminium
- Inlet ring: Sheet steel, galvanized


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 56	Drawings
on Page 182	Accessories
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com





Measuring requirements

Air performance measured according to: ISO 5801, installation category A, with ebm-papst inlet ring without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_p measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L_{wA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)			°C			
Voltage range 16-32 V DC												
A	①	24	2550	470	19,5	81	III	Any	-40...+70	Motor: IP 24 KM Electr.: IP 66/69 K	B	BA4)
	②	24	2431	538	22,4	78						
	③	24	2380	581	24,2	74						
	④	24	2402	556	23,1	76						
Voltage range 77-138 V DC												
B	①	110	2355	356	3,24	80	I	Shaft horizontal or rotor on bottom	-40...+60	IP 55 acc. to EN 60529	F	BA6)
	②	110	2290	428	3,99	75						
	③	110	2260	465	4,20	68						
	④	110	2300	450	4,09	72						
Nominal voltage range 380-480 V AC												
C	①	400	2650	538	0,88	83	I	Shaft horizontal or rotor on top	-40...+60	IP 55 acc. to EN 60529	F	BA7)
	②	400	2650	683	1,11	79						
	③	400	2650	750	1,20	75						
	④	400	2650	721	1,17	78						


Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve				
	Centrifugal fan		with support structure	
	Part number	Weight kg	Part number	Weight kg
A	R3G310RU2981	3,00	K3G310RU2981	9,40
B	R3G310RR12P1	4,60	K3G310RR12P1	10,50
C	R3G310RR05N1	5,20	K3G310RR05N1	11,10


A R3G310RU2981 (Centrifugal fan)

Dimensions in mm



A K3G310RU2981 (Centrifugal fan with support structure)

Dimensions in mm




- ① **Accessory part:** Inlet ring 31000-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 12 mm, tapping hole ready for self-tapping M6 screw
- ③ **Max. clearance of screw:** max. 10 mm, tapping hole ready for self-tapping M5 screw
- ④ **Max. clearance of screw:** max. 8 mm, tapping hole ready for self-tapping M4 screw
- ⑤ **Cable (halogen-free):** 2x BETAtrans® GKW R 2.5 mm², 2x crimped ferrules
2x BETAtrans® GKW R 1.0 mm², 2x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter


B R3G310RR12P1 (Centrifugal fan)

Dimensions in mm



B K3G310RR12P1 (Centrifugal fan with support structure)

Dimensions in mm




- ① **Accessory part:** Inlet ring 31000-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 16 mm
- ③ **Cable (halogen-free):** 3x BETAtrans[®] 3 GW flex, 4G 1.5 mm², 3x crimped ferrules
- ④ **Cable (halogen-free):** 7x BETAtrans[®] 3 GW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter


C R3G310RR05N1 (Centrifugal fan)

Dimensions in mm



C K3G310RR05N1 (Centrifugal fan with support structure)

Dimensions in mm




- ① **Accessory part:** Inlet ring 31000-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 16 mm
- ③ **Cable (halogen-free):** 4x BETAtrans[®] 3 GW flex, 4G 1.5 mm², 4x crimped ferrules
- ④ **Cable (halogen-free):** 7x BETAtrans[®] 3 GW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter

EC / DC centrifugal fans

backward curved, Ø 310 mm, Aluminium impeller



Material/surface

- Impeller: Sheet aluminium
- Rotor: Painted black
- Electronics housing: Die-cast aluminium
- Support structure: Aluminium
- Inlet ring: Sheet steel, galvanized


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 62	Drawings
on Page 182	Accessories
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements
 Air performance measured according to: ISO 5801, installation category A, with ebm-papst inlet ring without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L _{WA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)			°C			
Voltage range 77-138 V DC												
A	1	110	2915	995	9,00	88	I	Shaft horizontal or rotor on bottom	-40..+60	IP 55 acc. to EN 60529	F	BA6)
	2	110	2730	995	9,00	82						
	3	110	2650	995	9,00	77						
	4	110	2765	995	9,00	84						
Nominal voltage range 380-480 V AC												
B	1	400	3135	1229	1,89	90	I	Shaft horizontal or rotor on bottom	-40..+60	IP 55 acc. to EN 60529	F	BA7)
	2	400	3005	1300	2,00	85						
	3	400	2900	1300	2,00	80						
	4	400	2970	1300	2,00	85						


Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve	Centrifugal fan		with support structure	
	Part number	Weight kg	Part number	Weight kg
A	R3G310BE84S1	8,50	K3G310BE84S1	15,0
B	R3G310BE90N1	8,50	K3G310BE90N1	15,0


A R3G310BE84S1 (Centrifugal fan)

Dimensions in mm



A K3G310BE84S1 (Centrifugal fan with support structure)

Dimensions in mm




- ① **Accessory part:** Inlet ring 31570-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 16 mm
- ③ **Cable (halogen-free):** 3x BETAtrans[®] 3 GW flex, 4G 1.5 mm², 3x crimped ferrules
- ④ **Cable (halogen-free):** 7x BETAtrans[®] 3 GW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter


B R3G310BE90N1 (Centrifugal fan)

Dimensions in mm



B K3G310BE90N1 (Centrifugal fan with support structure)

Dimensions in mm



- ① **Accessory part:** Inlet ring 31570-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 16 mm
- ③ **Cable (halogen-free):** 4x BETAtrans[®] 3 GW flex, 4G 1.5 mm², 4x crimped ferrules
- ④ **Cable (halogen-free):** 7x BETAtrans[®] 3 GW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

Mounting Dimensions for centrifugal modules:
see "Accessories" chapter

EC / DC centrifugal fans

backward curved, $\varnothing 355$ mm



Material/surface

- Impeller: PA66 plastic, black
- Rotor: Painted black
- Electronics housing: Die-cast aluminium


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 66	Drawings
on Page 182	Accessories
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements

Air performance measured according to: ISO 5801, installation category A, with ebm-papst inlet ring without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L _{WA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)			°C			
Voltage range 77-138 V DC												
A	1	110	2035	475	4,32	81	I	Shaft horizontal or rotor on bottom	-40..+60	IP 55 acc. to EN 60529	F	BA6)
	2	110	1905	500	4,70	76						
	3	110	1830	500	4,70	70						
	4	110	1885	500	4,70	74						
B	1	110	2400	759	6,89	93	I	Shaft horizontal or rotor on bottom	-40..+60	IP 55 acc. to EN 60529	F	BA6)
	2	110	2285	880	8,00	85						
	3	110	2200	880	8,00	75						
	4	110	2270	880	8,00	78						
Nominal voltage range 380-480 V AC												
C	1	400	2400	777	1,20	90	I	Shaft horizontal or rotor on bottom	-40..+60	IP 55 acc. to EN 60529	F	BA7)
	2	400	2400	1037	1,59	83						
	3	400	2400	1100	1,70	75						
	4	400	2400	1056	1,62	77						



Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve	Centrifugal fan	
	Part number	Weight
A	R3G355RS13P1	5,50
B	R3G355RJ85S1	8,40
C	R3G333RJ76N1	8,40

A R3G355RS13P1 (Centrifugal fan)

Dimensions in mm





- ① **Accessory part:** Inlet ring 35500-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 16 mm
- ③ **Cable (halogen-free):** 3x BETAtrans[®] 3 GKW flex, 4G 1.5 mm², 3x crimped ferrules
- ④ **Cable (halogen-free):** 7x BETAtrans[®] 3 GKW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

B K3G355RJ85S1 (Centrifugal fan)

Dimensions in mm




- ① **Accessory part:** Inlet ring 35500-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 16 mm
- ③ **Cable (halogen-free):** 3x BETAtrans[®] 3 GKW flex, 4G 1.5 mm², 3x crimped ferrules
- ④ **Cable (halogen-free):** 7x BETAtrans[®] 3 GKW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

C R3G355RJ76N1 (Centrifugal fan)

Dimensions in mm




- ① **Accessory part:** Inlet ring 35500-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 16 mm
- ③ **Cable (halogen-free):** 4x BETAtrans® 3 GW flex, 4G 1.5 mm², 4x crimped ferrules
- ④ **Cable (halogen-free):** 7x BETAtrans® 3 GW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

EC / DC centrifugal fans

backward curved, Ø 400 mm, Aluminium impeller



Material/surface

- Impeller: Sheet aluminium
- Rotor: Painted black
- Electronics housing: Die-cast aluminium


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 70	Drawings
on Page 182	Accessories
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements


Air performance measured according to: ISO 5801, installation category A, with ebm-papst inlet ring without contact protection. Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L_{wA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)			°C			
Nominal voltage range 380-480 V AC												
A	1	400	2600	2400	3,70	95	I	Shaft horizontal or rotor on bottom	-40..+60	IP 55	F	BA8)
	2	400	2430	2400	3,70	89						
	3	400	2400	2400	3,70	84						
	4	400	2505	2372	3,67	88						

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan	
	Part number	Weight
A	R3G400BE08N1	15,10 kg



- ① **Accessory part:** Inlet ring 40070-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 20 mm
- ③ **Cable diameter:** min. 4 mm, max. 10 mm, Tightening torque 2 ± 0.3 Nm
- ④ **Tightening torque:** 1.5 ± 0.2 Nm

Pin assignment: see connection diagram



EC / DC axial fans

Ø 300 - Ø 500

ebmpapst

the engineer's choice

	Page
Ø 300-385	74
Ø 300-350 HyBlade	78
Ø 400 HyBlade	82
Ø 450 HyBlade	86
Ø 500 HyBlade	90

EC / DC axial fans

Ø 300-385 mm



Material/surface

- Housing and Impeller: PA66 plastic, black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Direction of air flow: "V" (sucking over rotor)
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 76	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com




Measuring requirements

Air performance measured according to: ISO 5801, installation category A, without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P _{ed}	Max. Input current I	Sound power level L _{WA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)			°C			
Voltage range 16-32 V DC												
A	1	24	3350	230	9,00	83	III	Any	-40...+85	Motor: IP 24 KM Electr.: IP 66/69 K	B	BA3)
	2	24	3350	277	10,7	84						
	3	24	3350	341	13,1	84						
	4	24	3350	379	14,6	87						
B	1	24	3140	450	17,7	88	III	Any	-40...+70	Motor: IP 24 KM Electr.: IP 66/69 K	B	BA4)
	2	24	3126	562	22,6	88						
	3	24	3059	622	25,2	88						
	4	24	2959	649	26,3	89						


Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Axial fan	
	Part number	Weight
A	W3G300BV2582	2,00 kg
B	W3G385CT6581	3,10 kg

A W3G300BV2582 (Axial fan)

Dimensions in mm




- ① Direction of air flow: "V"
- ② Cable: with plug tyco Junior Power Timer 1-962349-1, 6-pole, coded
Mating plug tyco 1-962312-1 not included in scope of delivery

Pin assignment: see connection diagram

B W3G385CT6581 (Axial fan)

Dimensions in mm



- ① Direction of air flow: "V"
- ② Cable (halogen-free):
 BETAtans[®] 3 GW 6 mm², 2x crimped ferrules (brown, black)
 BETAtans[®] GW R 1.0 mm², 2x crimped ferrules (yellow, white)

Pin assignment: see connection diagram

EC / DC axial fans

Ø 300-350 mm, HyBlade



Material/surface

- Impeller: PP plastic, black
- Housing: Painted black
- Rotor: Painted black
- Electronics housing: Die-cast aluminium


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Direction of air flow: "A"
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- According to EN 45545-2 only for outside the passenger compartment application
- Approvals: EAC

on Page 80	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements

Air performance measured according to: ISO 5801, installation category A, without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.



Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L _{WA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)			°C			
Voltage range 77-138 V DC												
A	1	110	2350	165	1,50	73	I	Any	-40..+60	IP 6K9K	B	BA5)
	2	110	2350	202	1,80	73						
	3	110	2325	230	2,00	73						
	4	110	2250	230	2,00	75						
B	1	110	1490	135	1,20	69	I	Any	-40..+60	IP 6K9K	B	BA5)
	2	110	1415	135	1,20	66						
	3	110	1350	135	1,20	63						
	4	110	1300	135	1,20	66						

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve	Axial fan	
	Part number	Weight
A	W3G300CT80P1	4,20 kg
B	W3G350CT81P1	4,80 kg





① Direction of air flow: "A"


② Cable (halogen-free):

BETAtrans® GW Flex R, 10G 1.0 mm², 10x crimped splices

Pin assignment: see connection diagram

B W3G350CT81P1 (Axial fan)

Dimensions in mm



- ① Direction of air flow: "A"
- ② Cable (halogen-free):
BETAtrans® GW Flex R, 10G 1.0 mm², 10x crimped splices

Pin assignment: see connection diagram

EC / DC axial fans

Ø 400 mm, HyBlade



Material/surface

- Impeller: PA66 plastic, sheet-metal plate painted black
- Housing: Sheet steel, galvanized and coated with black plastic
- Support ring: Stainless steel
- Rotor: Painted black
- Electronics housing: Die-cast aluminium


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Direction of air flow: "A"
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 84	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements


Air performance measured according to: ISO 5801, installation category A, without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L_{wA}	Max. back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Voltage range 77-138 V DC													
A	1	110	1695	404	3,70	79	170	I	Shaft horizontal or rotor on top	-40..+60	IP 55 acc. to EN 60529	F	BA5)
	2	110	1700	439	4,00	77							
	3	110	1690	460	4,20	74							
	4	110	1670	460	4,20	79							

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve	Axial fan		with round full nozzle	
	Part number	Weight	Part number	Weight
		kg		kg
A	A3G400BK13P3	4,70	W3G400CK13P3	10,50




- ① Direction of air flow: "A"
- ② Max. clearance of screw: max. 16 mm
- ③ Cable (halogen-free): 3x BETAtrans® 3 GW flex, 4G 1.5 mm², 3x crimped ferrules
- ④ Cable (halogen-free): 7x BETAtrans® 3 GW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

A W3G400CK13P3 (Axial fan with round full nozzle)

Dimensions in mm




- ① Direction of air flow: "A"
- ③ Cable (halogen-free): 3x BETAtrans® 3 GW flex, 4G 1.5 mm², 3x crimped ferrules
- ④ Cable (halogen-free): 7x BETAtrans® 3 GW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

EC / DC axial fans

Ø 450 mm, HyBlade



Material/surface

- Impeller: PA66 plastic, sheet-metal plate painted black
- Housing: Sheet steel, galvanized and coated with black plastic
- Support ring: Stainless steel
- Rotor: Painted black
- Electronics housing: Die-cast aluminium


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Direction of air flow: "A"
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 88	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements

Air performance measured according to: ISO 5801, installation category A, without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L_{wA}	Max. back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Voltage range 77-138 V DC													
A	1	110	1550	429	3,90	76	160	I	Shaft horizontal or rotor on top	-40..+60	IP 55 acc. to EN 60529	F	BA6)
	2	110	1550	490	4,50	72							
	3	110	1535	530	4,80	71							
	4	110	1500	530	4,80	75							
Nominal voltage range 380-480 V AC													
B	1	400	1500	391	0,66	76	150	I	Shaft horizontal or rotor on top	-40..+60	IP 55 acc. to EN 60529	F	BA7)
	2	400	1500	441	0,73	72							
	3	400	1500	481	0,78	70							
	4	400	1500	500	0,83	72							


Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve	Axial fan		with round full nozzle	
	Part number	Weight kg	Part number	Weight kg
A	A3G450BL17P3	5,00	W3G450CL17P3	12,00
B	A3G450BL12N1	5,30	W3G450CL12N1	12,30


A A3G450BL17P3 (Axial fan)

Dimensions in mm



A W3G450CL17P3 (Axial fan with round full nozzle)

Dimensions in mm




- ① Direction of air flow: "A"
- ② Max. clearance of screw: max. 16 mm
- ③ Cable (halogen-free): 3x BETAtans[®] 3 GKW flex, 4G 1.5 mm², 3x crimped ferrules
- ④ Cable (halogen-free): 7x BETAtans[®] 3 GKW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram


B A3G450BL12N1 (Axial fan)

Dimensions in mm



B W3G450CL12N1 (Axial fan with round full nozzle)

Dimensions in mm




- ① Direction of air flow: "A"
- ② Max. clearance of screw: max. 16 mm
- ③ Cable (halogen-free): 3x BETAtrens® 3 GKW flex, 4G 1.5 mm², 3x crimped ferrules
- ④ Cable (halogen-free): 7x BETAtrens® 3 GKW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram

EC / DC axial fans

Ø 500 mm, HyBlade



Material/surface

- Impeller: PA66 plastic
- Housing: Sheet steel, galvanized and coated with black plastic
- Support ring: Stainless steel
- Rotor: Painted black
- Electronics housing: Die-cast aluminium


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Direction of air flow: "A"
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 92	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements

Air performance measured according to: ISO 5801, installation category A, without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P _{ed}	Max. Input current I	Sound power level L _{WA}	Max. back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Voltage range 77-138 V DC													
A	1	110	1600	735	6,70	84	210	I	Shaft horizontal or rotor on top	-40...+60	IP 55 acc. to EN 60529	F	BA6)
	2	110	1600	862	7,80	83							
	3	110	1600	963	8,80	81							
	4	110	1600	1020	9,30	79							
Nominal voltage range 380-480 V AC													
B	1	400	1600	718	1,12	82	235	I	Shaft horizontal or rotor on top	-40...+60	IP 55 acc. to EN 60529	F	BA7)
	2	400	1600	847	1,31	79							
	3	400	1600	942	1,45	79							
	4	400	1600	1000	1,60	81							


Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve	Axial fan		with round full nozzle	
	Part number	Weight kg	Part number	Weight kg
A	A3G500BA73S1	7,40	W3G500CA73S1	15,40
B	A3G500BA74N1	7,40	W3G500CA74N1	15,40


A A3G500BA73S1 (Axial fan)

Dimensions in mm



A W3G500CA73S1 (Axial fan with round full nozzle)

Dimensions in mm




- ① Direction of air flow: "A"
- ② Max. clearance of screw: max. 16 mm
- ③ Cable (halogen-free): 3x BETAttrans® 3 GKW flex, 4G 1.5 mm², 3x crimped ferrules
- ④ Cable (halogen-free): 7x BETAttrans® 3 GKW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram


B A3G500BA74N1 (Axial fan)

Dimensions in mm



B W3G500CA74N1 (Axial fan with round full nozzle)

Dimensions in mm



- ① Direction of air flow: "A"
- ② Max. clearance of screw: max. 16 mm
- ③ Cable (halogen-free): 3x BETAtrans[®] 3 GW flex, 4G 1.5 mm², 3x crimped ferrules
- ④ Cable (halogen-free): 7x BETAtrans[®] 3 GW flex, 7x 0.5 mm², 7x crimped ferrules

Pin assignment: see connection diagram



DC compact fans

ebmpapst

the engineer's choice

	Page
Axial fan 6300 NTD	96
Centrifugal fan RLF 100	100

DC axial fan

Ø 172 x 51 mm



on Page 98	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com

Material/surface

- Impeller: Plastic, black
- Housing: Metal, black

Mechanical data


- Direction of rotation: Counter-clockwise viewed toward rotor
- Direction of air flow: Blowing over struts
- Installation position: Any
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Electrical data

- Protection class: III

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC




Measuring requirements



Air performance measured according to: ISO 5801, installation category A, without contact protection.
Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Nominal voltage	Speed n	Input power P_{ed}	Input current I	Sound power level L_{wA}	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
	VDC	rpm	W	A	dB(A)	°C			
Voltage range 16-36 V DC									
A	24	6000	90	3,75	79	-20..+70	IP 68	E	BA10)

Specification of nominal data: free blowing

Subject to change

Curve		
	Axial fan	
	Part number	Weight
		kg
A	6314N2TDHOU-305	0,85



- ① Dimensions: for mounting cutout
- ② Screw: Duo-Taptite according to DIN 7500, CM 4x8, Torx
- ③ Cable: 2x AWG 22 und 2x AWG 18, 4x crimped ferrules

Pin assignment: see connection diagram

DC centrifugal fan

□ 127 x 25 mm



Material/surface

- Impeller: Plastic
- Housing: Plastic
- Housing bottom: Sheet steel

Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Direction of air flow: axial sucking in, radial blowing out
- Installation position: Any
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral


Electrical data

- Protection class: III

Standards and approvals

- Conformity with standards: on request
- Approvals: EAC

on Page 102	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com




Measuring requirements


Air performance measured according to: ISO 5801, installation category A, with ebmpapst scroll housing without contact protection.
Intake-side sound level: L_{wA} measured according to ISO 10302. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Nominal voltage	Speed n	Input power P_{ed}	Input current I	Sound power level L_{wA}	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
	VDC	rpm	W	A	dB(A)	°C			
Voltage range 18-28 V DC									
A	24	5100	7,7	0,32	64	-20..+70	IP 54	E	BA11)

Specification of nominal data: free blowing

Subject to change

Curve		
	Centrifugal fan	
	Part number	Weight
		kg
A	RLF100-11/14PU-217	0,30



① Cable: 3x AWG 22

Pin assignment: see connection diagram



AC centrifugal fans *backward curved* Ø 190 - Ø 280

ebmpapst

the engineer's choice

	Page
Ø 190 RadiCal	106
Ø 220 RadiCal	110
Ø 250 RadiCal	114
Ø 280 RadiCal	118

AC centrifugal fans

backward curved, $\varnothing 190$ mm



Material/surface

- Impeller: PA66 plastic, sheet-metal plate painted black
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: axial

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 108	Drawings
on Page 182	Accessories
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com





Measuring requirements
 Air performance measured according to: ISO 5801, installation category A, with ebm-papst inlet ring without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L _{WA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)			°C			
Nominal voltage 400 V AC, 50 Hz												
A	1	400Y	2665	42	0,08	68	I	Shaft horizontal or rotor on bottom	-40..+80	IP 44 installation- and position-dependent	F	BA9)
	2	400Y	2620	46	0,09	63						
	3	400Y	2550	50	0,09	62						
	4	400Y	2630	45	0,08	65						
Nominal voltage 400 V AC, 60 Hz												
B	1	400Y	2945	59	0,09	70	I	Shaft horizontal or rotor on bottom	-40..+80	IP 44 installation- and position-dependent	F	BA9)
	2	400Y	2855	65	0,10	65						
	3	400Y	2750	70	0,11	63						
	4	400Y	2855	64	0,10	67						

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		Centrifugal fan	
		Part number	Weight
A		R2D190RB1811	1,60
B			



- ① **Accessory part:** Inlet ring 09576-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 5 mm
- ③ **Cable (halogen-free):** 9x BETrans® 3 GW flex, 9G 0.5 mm², 9x crimped splices

Pin assignment: see connection diagram

AC centrifugal fans

backward curved, $\varnothing 220$ mm



Material/surface

- Impeller: PA66 plastic, sheet-metal plate painted black
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: axial

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 112	Drawings
on Page 182	Accessories
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com





Measuring requirements
 Air performance measured according to: ISO 5801, installation category A, with ebm-papst inlet ring without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L_{wA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)			°C			
Nominal voltage 400 V AC, 50 Hz												
A	1	400 Δ	2800	98	0,25	70	I	Shaft horizontal or rotor on bottom	-40..+70	IP 44 installation- and position-dependent	F	BA9)
	2	400 Δ	2765	110	0,26	67						
	3	400 Δ	2750	120	0,27	65						
	4	400 Δ	2755	111	0,26	68						
B	1	400 Y	2455	67	0,11	67	I	Shaft horizontal or rotor on bottom	-40..+80	IP 44 installation- and position-dependent	F	BA9)
	2	400 Y	2360	76	0,12	63						
	3	400 Y	2300	82	0,13	61						
	4	400 Y	2355	77	0,12	64						
Nominal voltage 480 V AC, 60 Hz												
C	1	480 Δ	3315	151	0,28	75	I	Shaft horizontal or rotor on bottom	-40..+60	IP 44 installation- and position-dependent	F	BA9)
	2	480 Δ	3260	171	0,29	71						
	3	480 Δ	3200	190	0,31	69						
	4	480 Δ	3255	173	0,29	73						
D	1	480 Y	2825	108	0,14	71	I	Shaft horizontal or rotor on bottom	-40..+80	IP 44 installation- and position-dependent	F	BA9)
	2	480 Y	2705	120	0,16	67						
	3	480 Y	2600	130	0,17	64						
	4	480 Y	2690	121	0,16	68						

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan	
	Part number	Weight
		kg
	A B C D	R2D220RC3611



- ① **Accessory part:** Inlet ring 09609-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 5 mm
- ③ **Cable (halogen-free):** 9x BETAtrans® 3 GW flex, 9G 0.5 mm², 9x crimped splices

Pin assignment: see connection diagram

AC centrifugal fans

backward curved, $\varnothing 250$ mm



Material/surface

- Impeller: PA66 plastic, sheet-metal plate painted black
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: variabel

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 116	Drawings
on Page 182	Accessories
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com




Measuring requirements


Air performance measured according to: ISO 5801, installation category A, with ebm-papst inlet ring without contact protection. Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P _{ed}	Max. Input current I	Sound power level L _{WA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)			°C			
Nominal voltage 400 V AC, 50 Hz												
A	1	400 Δ	2755	174	0,31	78	I	Shaft horizontal or rotor on bottom	-40..+80	IP 44 installation- and position-dependent	F	BA9)
	2	400 Δ	2730	192	0,33	74						
	3	400 Δ	2700	215	0,36	70						
	4	400 Δ	2720	199	0,34	72						
B	1	400 Y	2300	140	0,22	74	I	Shaft horizontal or rotor on bottom	-40..+80	IP 44 installation- and position-dependent	F	BA9)
	2	400 Y	2235	148	0,23	69						
	3	400 Y	2150	160	0,24	64						
	4	400 Y	2200	150	0,24	67						
Nominal voltage 480 V AC, 60 Hz												
C	1	480 Δ	3245	286	0,40	82	I	Shaft horizontal or rotor on bottom	-40..+75	IP 44 installation- and position-dependent	F	BA9)
	2	480 Δ	3195	324	0,44	78						
	3	480 Δ	3150	355	0,48	74						
	4	480 Δ	3215	307	0,42	78						
D	1	480 Y	2600	214	0,29	77	I	Shaft horizontal or rotor on bottom	-40..+75	IP 44 installation- and position-dependent	F	BA9)
	2	480 Y	2475	230	0,31	71						
	3	480 Y	2350	240	0,32	66						
	4	480 Y	2515	222	0,30	72						

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan	
	Part number	Weight
		kg
	A B C D	R2D250RC1011



- ① **Accessory part:** Inlet ring 96359-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 10 mm
- ③ **Cable (halogen-free):** 9x BETAtrans® 3 GW flex, 9G 0.5 mm², 9x crimped splices

Pin assignment: see connection diagram

AC centrifugal fans

backward curved, $\varnothing 280$ mm



Material/surface

- Impeller: PA66 plastic, sheet-metal plate painted black
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: variabel

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 120	Drawings
on Page 182	Accessories
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements




Air performance measured according to: ISO 5801, installation category A, with ebm-papst inlet ring without contact protection.
 Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L_{wA}	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC										
Nominal voltage 400 V AC, 50 Hz												
A	1	400 Δ	2635	448	0,76	83	I	Shaft horizontal or rotor on bottom	-40..+60	IP 44 installation- and position-dependent	F	BA9)
	2	400 Δ	2565	509	0,85	78						
	3	400 Δ	2500	535	0,90	73						
	4	400 Δ	2580	480	0,81	76						
B	1	400 Y	2010	300	0,47	76	I	Shaft horizontal or rotor on bottom	-40..+50	IP 44 installation- and position-dependent	F	BA9)
	2	400 Y	1880	322	0,50	70						
	3	400 Y	1800	325	0,50	65						
	4	400 Y	1915	307	0,48	68						

Values set in blue are nominal data at operating point with maximum load.



Subject to change

Curve	Centrifugal fan	
	Part number	Weight
A	R2D280RB0811	4,70
B		



- ① **Accessory part:** Inlet ring 28000-2-4013, not included in scope of delivery
Dimensions: see "Accessories" chapter
- ② **Max. clearance of screw:** max. 10 mm
- ③ **Cable (halogen-free):** 9x BETAtrans[®] 3 GKW flex, 9G 0.5 mm², 9x crimped splices

Pin assignment: see connection diagram



AC centrifugal fans *forward curved with housing* Ø 120 - Ø 280, single-intake

ebmpapst

the engineer's choice

	Page
Ø 120 (2-pole)	124
Ø 140 (2-pole)	128
Ø 160 (2-pole)	132
Ø 180 (2-pole)	136
Ø 180 (4-pole)	140
Ø 200 (4-pole)	144
Ø 225 (4-pole)	148
Ø 250 (4-pole)	152

AC centrifugal fans

forward curved with housing, \varnothing 120 mm



Material/surface

- Impeller: Sheet steel galvanized
- Housing: Die-cast aluminium
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: axial

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 126	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com




Measuring requirements


Air performance measured according to: ISO 5801, installation category A, with ebm-papst scroll housing without contact protection. Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L _{WA}	Min. Back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Nominal voltage 400 V AC, 50 Hz													
A	1	400Y	2250	69	0,13	68	0	I	Shaft horizontal or rotor on bottom	-40..+80	IP 44 installation- and position-dependent	F	BA9)
	2	400Y	2440	59	0,12	66							
	3	400Y	2540	53	0,12	66							
	4	400Y	2655	46	0,12	65							
Nominal voltage 480 V AC, 60 Hz													
B	1	480Y	2600	100	0,16	71	0	I	Shaft horizontal or rotor on bottom	-40..+80	IP 44 installation- and position-dependent	F	BA9)
	2	480Y	2905	80	0,13	70							
	3	480Y	3090	66	0,13	70							
	4	480Y	3230	57	0,12	69							

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan with housing	
	Part number	Weight
		kg
A	G2D120AA2203	2,20
B		



① Cable (halogen-free): BETAttrans® GKW flex R, 9G 0.5 mm², 9x crimped splices

Pin assignment: see connection diagram

AC centrifugal fans

forward curved with housing, \varnothing 140 mm



Material/surface

- Impeller: Sheet steel galvanized
- Housing: Die-cast aluminium
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: axial

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 130	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements


Air performance measured according to: ISO 5801, installation category A, with ebm-papst scroll housing without contact protection. Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P _{ed}	Max. Input current I	Sound power level L _{WA}	Min. Back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Nominal voltage 400 V AC, 50 Hz													
A	1	400 Δ	2300	145	0,22	76	0	I	Shaft horizontal or rotor on bottom	-40..+80	IP 44 installation- and position-dependent	F	BA9)
	2	400 Δ	2425	125	0,20	74							
	3	400 Δ	2505	111	0,18	72							
	4	400 Δ	2640	87	0,15	70							
B	1	400 Y	1600	80	0,13	66	0	I	Shaft horizontal or rotor on bottom	-40..+80	IP 44 installation- and position-dependent	F	BA9)
	2	400 Y	1725	76	0,12	65							
	3	400 Y	1835	71	0,11	64							
	4	400 Y	2090	60	0,09	64							
Nominal voltage 480 V AC, 60 Hz													
C	1	480 Δ	2650	225	0,29	79	0	I	Shaft horizontal or rotor on bottom	-40..+80	IP 44 installation- and position-dependent	F	BA9)
	2	480 Δ	2785	198	0,26	77							
	3	480 Δ	2960	166	0,22	75							
	4	480 Δ	3110	134	0,18	74							
D	1	480 Y	1750	120	0,15	68	0	I	Shaft horizontal or rotor on bottom	-40..+80	IP 44 installation- and position-dependent	F	BA9)
	2	480 Y	1925	110	0,14	67							
	3	480 Y	2140	100	0,13	67							
	4	480 Y	2420	87	0,11	68							

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan with housing	
	Part number	Weight
		kg
	A B C D	G2D140AC3803



① Cable (halogen-free): BETrans[®] GWK flex R, 9G 0.5 mm², 9x crimped splices

Pin assignment: see connection diagram

AC centrifugal fans

forward curved with housing, $\varnothing 160$ mm



Material/surface

- Impeller: Sheet steel galvanized
- Housing: Die-cast aluminium
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: axial

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 134	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements




Air performance measured according to: ISO 5801, installation category A, with ebm-papst scroll housing without contact protection. Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P _{ed}	Max. Input current I	Sound power level L _{WA}	Min. Back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Nominal voltage 400 V AC, 50 Hz													
A	1	400 Δ	2200	320	0,48	80	0	I	Shaft horizontal or rotor on bottom	-40..+55	IP 44 installation- and position-dependent	F	BA9)
	2	400 Δ	2355	269	0,41	78							
	3	400 Δ	2510	221	0,34	76							
	4	400 Δ	2680	160	0,27	74							
B	1	400 Y	1350	160	0,24	67	0	I	Shaft horizontal or rotor on bottom	-40..+55	IP 44 installation- and position-dependent	F	BA9)
	2	400 Y	1555	150	0,23	67							
	3	400 Y	1765	137	0,21	67							
	4	400 Y	2075	115	0,18	67							
Nominal voltage 400 V AC, 60 Hz													
C	1	400 Δ	2600	305	0,46	76	400	I	Shaft horizontal or rotor on bottom	-40..+50	IP 44 installation- and position-dependent	F	BA9)
	2	400 Δ	2840	254	0,39	76							
	3	400 Δ	3105	187	0,29	78							
	4	400 Δ	3150	179	0,28	79							
D	1	400 Y	1650	155	0,24	64	155	I	Shaft horizontal or rotor on bottom	-40..+50	IP 44 installation- and position-dependent	F	BA9)
	2	400 Y	1875	144	0,22	65							
	3	400 Y	2180	129	0,20	69							
	4	400 Y	2535	109	0,17	73							

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan with housing	
	Part number	Weight
		kg
	A B C D	G2D160AF1203



- ① Cable (halogen-free): BETAttrans[®] GKW flex R, 9G 0.5 mm², 9x crimped splices
- ② For self-tapping M4 screws

Pin assignment: see connection diagram

AC centrifugal fans

forward curved with housing, $\varnothing 180$ mm



Material/surface

- Impeller: Sheet steel galvanized
- Housing: Die-cast aluminium
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: axial

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 138	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements




Air performance measured according to: ISO 5801, installation category A, with ebm-papst scroll housing without contact protection. Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L_{wA}	Min. Back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Nominal voltage 400 V AC, 50 Hz													
A	1	400 Δ	2150	450	0,70	83	0	I	Shaft horizontal or rotor on bottom	-40..+70	IP 44 installation- and position-dependent	F	BA9)
	2	400 Δ	2340	384	0,60	81							
	3	400 Δ	2515	301	0,48	78							
	4	400 Δ	2665	226	0,38	76							
B	1	400 Y	1400	240	0,37	71	0	I	Shaft horizontal or rotor on bottom	-40..+70	IP 44 installation- and position-dependent	F	BA9)
	2	400 Y	1585	222	0,36	70							
	3	400 Y	1825	197	0,31	70							
	4	400 Y	2110	163	0,26	70							
Nominal voltage 480 V AC, 60 Hz													
C	1	480 Δ	2700	580	0,75	83	400	I	Shaft horizontal or rotor on bottom	-40..+45	IP 44 installation- and position-dependent	F	BA9)
	2	480 Δ	2850	510	0,67	82							
	3	480 Δ	3015	423	0,56	81							
	4	480 Δ	3130	357	0,48	80							
D	1	480 Y	1750	300	0,40	72	160	I	Shaft horizontal or rotor on bottom	-40..+45	IP 44 installation- and position-dependent	F	BA9)
	2	480 Y	1925	285	0,38	72							
	3	480 Y	2140	263	0,35	72							
	4	480 Y	2355	239	0,32	73							

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan with housing	
	Part number	Weight
		kg
	A B C D	G2D180AB1003



- ① Cable (halogen-free): BETrans[®] GKW flex R, 9G 0.5 mm², 9x crimped splices
- ② For self-tapping M₄ screws

Pin assignment: see connection diagram

AC centrifugal fans

forward curved with housing, \varnothing 180 mm



Material/surface

- Impeller: Sheet steel galvanized
- Housing: Sheet steel galvanized
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: variabel

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 142	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com




Measuring requirements



Air performance measured according to: ISO 5801, installation category A, with ebm-papst scroll housing without contact protection. Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L_{wA}	Min. Back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Nominal voltage 400 V AC, 50 Hz													
A	1	400 Δ	1300	190	0,40	72	0	I	Shaft horizontal or rotor on bottom	-40..+65	IP 44 installation- and position-dependent	F	BA9)
	2	400 Δ	1350	162	0,34	70							
	3	400 Δ	1385	136	0,32	67							
	4	400 Δ	1425	106	0,31	64							
B	1	400 Y	970	120	0,21	65	0	I	Shaft horizontal or rotor on bottom	-40..+85	IP 44 installation- and position-dependent	F	BA9)
	2	400 Y	1050	107	0,19	63							
	3	400 Y	1145	93	0,16	62							
	4	400 Y	1265	71	0,13	61							
Nominal voltage 480 V AC, 60 Hz													
C	1	480 Δ	1500	300	0,47	76	0	I	Shaft horizontal or rotor on bottom	-40..+50	IP 44 installation- and position-dependent	F	BA9)
	2	480 Δ	1580	253	0,40	74							
	3	480 Δ	1635	207	0,36	71							
	4	480 Δ	1705	145	0,32	68							
D	1	480 Y	1050	165	0,25	67	0	I	Shaft horizontal or rotor on bottom	-40..+60	IP 44 installation- and position-dependent	F	BA9)
	2	480 Y	1160	155	0,23	66							
	3	480 Y	1290	137	0,20	65							
	4	480 Y	1495	101	0,15	65							

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan with housing	
	Part number	Weight
		kg
	A B C D	G4D180FF2402



① Cable (halogen-free): BETAtans[®] 3 GKW flex, 9G 0.75 mm², 9x crimped splices

Pin assignment: see connection diagram

AC centrifugal fans

forward curved with housing, \varnothing 200 mm



Material/surface

- Impeller: Sheet steel galvanized
- Housing: Sheet steel galvanized
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: variabel

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 146	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements


Air performance measured according to: ISO 5801, installation category A, with ebm-papst scroll housing without contact protection. Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P _{ed}	Max. Input current I	Sound power level L _{WA}	Min. Back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Nominal voltage 400 V AC, 50 Hz													
A	1	400 Δ	1250	300	0,55	74	0	I	Shaft horizontal or rotor on bottom	-40..+65	IP 44 installation- and position-dependent	F	BA9)
	2	400 Δ	1325	253	0,48	72							
	3	400 Δ	1360	215	0,44	70							
	4	400 Δ	1415	149	0,39	67							
B	1	400 Y	950	185	0,31	67	0	I	Shaft horizontal or rotor on bottom	-40..+65	IP 44 installation- and position-dependent	F	BA9)
	2	400 Y	1010	168	0,28	65							
	3	400 Y	1090	152	0,25	65							
	4	400 Y	1250	109	0,19	64							
Nominal voltage 480 V AC, 60 Hz													
C	1	480 Δ	1600	325	0,55	74	250	I	Shaft horizontal or rotor on bottom	-40..+60	IP 44 installation- and position-dependent	F	BA9)
	2	480 Δ	1635	288	0,47	73							
	3	480 Δ	1665	246	0,44	72							
	4	480 Δ	1690	213	0,41	71							
D	1	480 Y	1200	220	0,31	66	140	I	Shaft horizontal or rotor on bottom	-40..+60	IP 44 installation- and position-dependent	F	BA9)
	2	480 Y	1290	200	0,28	67							
	3	480 Y	1375	180	0,25	67							
	4	480 Y	1445	160	0,23	67							

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan with housing	
	Part number	Weight
		kg
	A B C D	G4D200BL1903



① Cable (halogen-free): BETrans[®] 3 GKW flex, 9G 0.75 mm², 9x crimped splices

Pin assignment: see connection diagram

AC centrifugal fans

forward curved with housing, \varnothing 225 mm



Material/surface

- Impeller: Sheet steel galvanized
- Housing: Sheet steel galvanized
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: variabel

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 150	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com




Measuring requirements




Air performance measured according to: ISO 5801, installation category A, with ebm-papst scroll housing without contact protection. Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L_{wA}	Min. Back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Nominal voltage 400 V AC, 50 Hz													
A	1	400 Δ	1350	405	0,80	80	0	I	Shaft horizontal or rotor on bottom	-40..+80	IP 54	F	BA9)
	2	400 Δ	1375	347	0,70	77							
	3	400 Δ	1405	281	0,63	75							
	4	400 Δ	1435	207	0,57	71							
B	1	400 Y	1050	300	0,50	73	0	I	Shaft horizontal or rotor on bottom	-40..+80	IP 54	F	BA9)
	2	400 Y	1130	266	0,47	73							
	3	400 Y	1215	224	0,39	71							
	4	400 Y	1310	167	0,30	69							
Nominal voltage 480 V AC, 60 Hz													
C	1	480 Δ	1600	600	0,90	82	100	I	Shaft horizontal or rotor on bottom	-40..+50	IP 54	F	BA9)
	2	480 Δ	1640	512	0,81	80							
	3	480 Δ	1670	436	0,72	79							
	4	480 Δ	1700	346	0,64	76							
D	1	480 Y	1200	410	0,60	74	55	I	Shaft horizontal or rotor on bottom	-40..+50	IP 54	F	BA9)
	2	480 Y	1285	379	0,56	74							
	3	480 Y	1370	341	0,50	73							
	4	480 Y	1485	280	0,41	73							

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan with housing	
	Part number	Weight
		kg
	A B C D	G4D225FK2002



① Cable (halogen-free): BETAtrans[®] 3 GW flex, 9G 0.75 mm², 9x crimped splices

Pin assignment: see connection diagram

AC centrifugal fans

forward curved with housing, \varnothing 250 mm



Material/surface

- Impeller: Sheet steel galvanized
- Housing: Sheet steel galvanized
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: variabel

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 154	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com




Measuring requirements



Air performance measured according to: ISO 5801, installation category A, with ebm-papst scroll housing without contact protection. Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P _{ed}	Max. Input current I	Sound power level L _{WA}	Min. Back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Nominal voltage 400 V AC, 50 Hz													
A	1	400 Δ	1340	575	1,10	82	0	I	Shaft horizontal or rotor on bottom	-40..+70	IP 54	F	BA9)
	2	400 Δ	1375	482	0,98	80							
	3	400 Δ	1405	386	0,87	76							
	4	400 Δ	1445	248	0,75	72							
B	1	400 Y	1050	410	0,70	76	0	I	Shaft horizontal or rotor on bottom	-40..+70	IP 54	F	BA9)
	2	400 Y	1135	359	0,63	75							
	3	400 Y	1215	306	0,54	73							
	4	400 Y	1340	200	0,37	70							
Nominal voltage 480 V AC, 60 Hz													
C	1	480 Δ	1620	770	1,20	83	200	I	Shaft horizontal or rotor on bottom	-40..+50	IP 54	F	BA9)
	2	480 Δ	1660	628	1,03	80							
	3	480 Δ	1685	523	0,93	78							
	4	480 Δ	1715	411	0,82	76							
D	1	480 Y	1230	535	0,80	76	115	I	Shaft horizontal or rotor on bottom	-40..+50	IP 54	F	BA9)
	2	480 Y	1350	474	0,70	75							
	3	480 Y	1440	415	0,61	74							
	4	480 Y	1535	338	0,50	73							

Values set in blue are nominal data at operating point with maximum load.


Subject to change

Curve		
	Centrifugal fan with housing	
	Part number	Weight
		kg
	A B C D	G4D250DC1402



① Cable (halogen-free): BETrans[®] 3 GKW flex, 9G 0.75 mm², 9x crimped splices

Pin assignment: see connection diagram



AC centrifugal fans *forward curved with housing* Ø 133 - Ø 200, dual-intake

ebmpapst

the engineer's choice

	Page
Ø 133 (2-pole)	158
Ø 146 (2-pole)	162
Ø 160 (2-pole)	166
Ø 180 (4-pole)	170
Ø 200 (4-pole)	174

AC centrifugal fans

forward curved with housing, \varnothing 133 mm



Material/surface

- Impeller: Sheet steel galvanized
- Housing: Sheet steel galvanized
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 160	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com




Measuring requirements



Air performance measured according to: ISO 5801, installation category A, with ebm-papst scroll housing without contact protection. Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L_{wA}	Min. Back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Nominal voltage 400 V AC, 50 Hz													
A	1	400 Δ	2250	195	0,31	70	210	I	Shaft horizontal	-40..+70	IP 44	F	BA9)
	2	400 Δ	2470	154	0,25	69							
	3	400 Δ	2615	122	0,21	69							
	4	400 Δ	2695	101	0,19	70							
B	1	400 Y	1550	105	0,16	60	95	I	Shaft horizontal	-40..+70	IP 44	F	BA9)
	2	400 Y	1765	95	0,15	61							
	3	400 Y	2000	82	0,13	63							
	4	400 Y	2165	73	0,11	65							
Nominal voltage 400 V AC, 60 Hz													
C	1	400 Δ	2350	240	0,37	70	230	I	Shaft horizontal	-40..+50	IP 44	F	BA9)
	2	400 Δ	2725	186	0,29	72							
	3	400 Δ	2905	158	0,25	72							
	4	400 Δ	3025	138	0,22	73							
D	1	400 Y	1450	115	0,18	58	85	I	Shaft horizontal	-40..+50	IP 44	F	BA9)
	2	400 Y	1820	103	0,16	61							
	3	400 Y	2025	95	0,15	63							
	4	400 Y	2185	89	0,14	65							

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan with housing	
	Part number	Weight
		kg
	A B C D	D2D133DB4003



① Cable (halogen-free): BETAtrans[®] GKW flex, 9G 0.5 mm², 9x crimped splices

Pin assignment: see connection diagram

AC centrifugal fans

forward curved with housing, \varnothing 146 mm



Material/surface

- Impeller: Sheet steel galvanized
- Housing: Sheet steel galvanized
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 164	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com




Measuring requirements



Air performance measured according to: ISO 5801, installation category A, with ebm-papst scroll housing without contact protection. Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L_{wA}	Min. Back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Nominal voltage 400 V AC, 50 Hz													
A	1	400 Δ	2300	265	0,41	72	300	I	Shaft horizontal	-40..+60	IP 44	F	BA9)
	2	400 Δ	2495	212	0,34	72							
	3	400 Δ	2610	178	0,29	73							
	4	400 Δ	2720	138	0,24	75							
B	1	400 Y	1500	150	0,23	61	130	I	Shaft horizontal	-40..+60	IP 44	F	BA9)
	2	400 Y	1735	136	0,21	63							
	3	400 Y	1920	124	0,19	66							
	4	400 Y	2180	104	0,16	70							
Nominal voltage 400 V AC, 60 Hz													
C	1	400 Δ	2500	305	0,47	73	360	I	Shaft horizontal	-40..+45	IP 44	F	BA9)
	2	400 Δ	2690	270	0,42	74							
	3	400 Δ	2875	235	0,36	76							
	4	400 Δ	3040	196	0,31	78							
D	1	400 Y	1500	150	0,24	60	125	I	Shaft horizontal	-40..+45	IP 44	F	BA9)
	2	400 Y	1690	146	0,22	63							
	3	400 Y	1890	138	0,21	66							
	4	400 Y	2110	129	0,20	69							

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan with housing	
	Part number	Weight
		kg
A	D2D146AA1203	4,40
B		
C		
D		



① Cable (halogen-free): BETrans[®] GW flex R, 9G 0.5 mm², 9x crimped splices

Pin assignment: see connection diagram

AC centrifugal fans

forward curved with housing, \varnothing 160 mm



Material/surface

- Impeller: Sheet steel galvanized
- Housing: Sheet steel galvanized
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 168	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com






Measuring requirements
 Air performance measured according to: ISO 5801, installation category A, with ebm-papst scroll housing without contact protection.
 Intake-side sound level: L_{wA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L_{wA}	Min. Back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Nominal voltage 400 V AC, 50 Hz													
A	1	400Y	2700	700	1,28	80	400	I	Shaft horizontal	-40..+75	IP 00	F	BA9)
	2	400Y	2795	523	1,04	80							
	3	400Y	2835	428	0,93	81							
	4	400Y	2870	355	0,85	82							
Nominal voltage 400 V AC, 60 Hz													
B	1	400Y	3000	1055	1,70	83	500	I	Shaft horizontal	-40..+65	IP 00	F	BA9)
	2	400Y	3160	807	1,33	83							
	3	400Y	3240	689	1,15	84							
	4	400Y	3315	560	0,97	86							

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan with housing	
	Part number	Weight
		kg
A	D2D160BE0203	9,80
B		



① Cable (halogen-free): BETAtans[®] GKW flex R, 9G 0.5 mm², 6x crimped splices

Pin assignment: see connection diagram

AC centrifugal fans

forward curved with housing, \varnothing 180 mm



Material/surface

- Impeller: Sheet steel galvanized
- Housing: Sheet steel galvanized
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 172	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com




Measuring requirements



Air performance measured according to: ISO 5801, installation category A, with ebm-papst scroll housing without contact protection. Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L_{wA}	Min. Back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Nominal voltage 400 V AC, 50 Hz													
A	1	400Y	1100	255	0,50	73	0	I	Shaft horizontal	-40..+70	IP 54	F	BA9)
	2	400Y	1175	216	0,42	70							
	3	400Y	1245	181	0,38	68							
	4	400Y	1345	125	0,33	64							
Nominal voltage 480 V AC, 60 Hz													
B	1	480Y	1370	320	0,50	73	100	I	Shaft horizontal	-40..+70	IP 54	F	BA9)
	2	480Y	1450	274	0,44	71							
	3	480Y	1515	232	0,40	70							
	4	480Y	1575	194	0,37	69							

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan with housing	
	Part number	Weight
		kg
A	D4D180BB0903	9,10
B		



① Cable (halogen-free): BETAtrans[®] 3 GKW flex, sw 6G 0.5 mm², 6x crimped splices

Pin assignment: see connection diagram

AC centrifugal fans

forward curved with housing, \varnothing 200 mm



Material/surface

- Impeller: Sheet steel galvanized
- Housing: Sheet steel galvanized
- Rotor: Painted black


Mechanical data

- Direction of rotation: Clockwise viewed toward rotor
- Mode: Continuous operation (S1)
- Mounting: Maintenance-free ball bearings
- Cable exit: lateral

Standards and approvals

- Conformity with standards: see page 6
- Approvals: EAC

on Page 176	Drawings
on Page 192	Connection diagrams and technical features
on Page 204	Technical parameters & scope
More at	www.ebmpapst.com



Measuring requirements



Air performance measured according to: ISO 5801, installation category A, with ebm-papst scroll housing without contact protection. Intake-side sound level: L_{pA} according to ISO 13347, L_{pA} measured at 1 m distance from fan axis. The values given are only applicable under the specified measuring conditions and may differ depending on the installation conditions. In the event of deviation from the standard configuration, the parameters must be checked in installed condition.

Curve	Operating point	Nominal voltage	Speed n	Max. Input power P_{ed}	Max. Input current I	Sound power level L_{wA}	Min. Back pressure	Protection class	Installation position	Perm. ambient temp.	Degree of protection	Insulation class	Conn. diagram
		VDC	rpm	W	A	dB(A)	Pa			°C			
Nominal voltage 400 V AC, 50 Hz													
A	1	400Y	1100	405	0,75	76	0	I	Shaft horizontal	-40...+65	IP 54	F	BA9)
	2	400Y	1185	345	0,66	73							
	3	400Y	1250	286	0,59	70							
	4	400Y	1330	211	0,52	67							
Nominal voltage 480 V AC, 60 Hz													
B	1	480Y	1370	500	0,80	75	150	I	Shaft horizontal	-40...+60	IP 54	F	BA9)
	2	480Y	1445	445	0,70	74							
	3	480Y	1505	384	0,64	73							
	4	480Y	1565	323	0,58	71							

Values set in blue are nominal data at operating point with maximum load.

Subject to change

Curve		
	Centrifugal fan with housing	
	Part number	Weight
		kg
A	D4D200BA0103	10,80
B		



① Cable (halogen-free): BETAtans[®] 3 GW flex, sw 6G 0.5 mm², 6x crimped splices


Pin assignment: see connection diagram

it's time for tomorrow

We extend the limits of what's feasible every day. Our longstanding engineering expertise gives us the capability to lead the way in technological development. We have a range of products with an enormous potential for efficient allround solutions to meet each individual facet of your needs. We're your partner at every phase of the process chain, coming up with new ideas while keeping the big picture in mind. We have a wide range of product-specific knowledge in building the right drive designs for you. We're always in tune with the times to offer you excellent ideas, outstanding innovations and hands-on-service.

EQ³ – Inclusive of Economic Quality

EQ³ is the ebm-papst concept for the future, which combines intelligent drive solutions with important performance characteristics. All gear motors impress with unsurpassed values in terms of lifetime and performance, and move the future through environmental protection with the highest level of efficiency. Creating the future together – it's time for tomorrow!



Drive concepts ebm-papst

Powerful, Safe, Reliable

ebmpapst

the engineer's choice

	Page
Solutions for the most demanding requirements	180

Solutions for the most demanding requirements

Drive concepts with future

The highest level of safety for passenger transportation

Personal safety plays an especially important role in the transportation of passengers in public transit. In this context, the focus is on components for moving entry aids and door systems, which have their own special requirements with regard to performance.

Demographic change also puts high demands on systems that automatically open and close doors, and with respect the management of barriers.

The right drive concept at every step

With its technologically exemplary drive concepts, ebm-papst implements innovative and reliable gear motors for many conceivable motion requirements in the area of passenger transportation.

Mature technologies, maximum efficiency and reliability along with extreme resilience and lifetime are supplemented by technical refinements and a broad service range.

Comprehensive development services and decades of experience stand for extraordinary solutions that also allow for the combination of planetary, spur and angle gearheads.

Trailblazing drive solutions

Motion components are subject to great loads, especially when it comes to train operations, and result in important aspects in terms of implementation:


- Target-oriented implementation of demanding market requirements in view of performance density and durability
- Compliance with specifications and technical requirement by legislation and standards
- High corrosion-resistance and functional safety even in extreme weather conditions
- Vibration resistance to compensate for vibration responses

ebm-papst considers these requirements the main criteria for the design of these intelligent and powerful gear motors. They are virtually unbeatable when it comes to durability, quality and safety, and hence represent a safe and profitable investment.

Services for sophisticated needs

Our well-rounded range of effective services adds to your advantages. We assume responsibility for the finished, delivered product providing you with reliability, attentiveness and excellent performance throughout the entire product design and manufacturing cycles. Our employees, who daily live up their commitment to service, are your guarantee for success.

The bottom line is service unparalleled in the market.




A Door drives:



One-stage planetary gearhead for train doors.



Planetary gearhead motor Performax 63 for sliding and locking.



Angle/planetary gearhead combination for the safe sliding and locking of train doors.



Special drive for sliding plug door drives with two outputs.

B Drives for entry aids:



Three-stage spur gearheads for the sliding and holding of sliding steps.



Special angle gearhead with combined planetary/crown technology for folding steps and ramps.

C Special applications:



Two-stage EtaCrown gearhead with special reinforcements for windscreen wipers.



One-stage EtaCrown angle gearhead for tilt technology.



Accessories

for rail technology

ebmpapst

the engineer's choice

	Page
FlowGrid air inlet grill	184
Mounting dimensions for centrifugal modules	185
Inlet rings for centrifugal fans	186

FlowGrid air inlet grill

efficient noise reduction



The air performance of ebm-papst fans is not the only thing measured on the state-of-the-art, in-house test stand.

The acoustic behavior of the fans is also examined and the measuring results are included in the technical documentation. Please note that the measurements are taken under ideal conditions with undisturbed inflow and outflow. If the fans are later installed in applications where limited space is available, the noise information listed in the documentation will probably not be applicable.

In order to minimize the negative impact of the installation situation, ebm-papst offers the FlowGrid airinlet guard shown here. It is mounted on the fan's intake side and effectively reduces the noise in the fan's overall frequency range; especially the disturbing tonal noise in the low frequency range.

The result is a far lower sound pressure level and pleasant running noise.


Since the level of noise reduction is dependent on the installation circumstances, it is not possible to provide generally applicable information here.

FlowGrid air inlet grill

Part number	Fan size	Ø B (mm)	Ø C (mm)	Ø E (mm)	S (mm)	H (mm)	N* (Nm)	Weight (g)
20282-2-2957	250 280	280	245 -261	4,5	3,5	40	2 ± 0,5 Nm	144
25312-2-2957	310	315	288 -292	5,5	3,5	49	2 ± 0,5 Nm	232

Subject to change

* Recommended tightening torque for fastening screws



Would you like to find out more?

If you need an installation guide or more information about the dimensions, go to:


www.ebmpapst.com/flowgrid-manual

or scan the QR code below:



Mounting dimensions

for EC centrifugal modules $\varnothing 250$, $\varnothing 280$, $\varnothing 310$



Inlet rings



for centrifugal fans



Fan size 190, RadiCal

Part number



09576-2-4013




Fan size 220, RadiCal

Part number


09609-2-4013




Fan size 250, RadiCal
Part number
96359-2-4013



Fan size 250, Aluminium impeller
Part number
25070-2-4013



Fan size 280, RadiCal
Part number
28000-2-4013




Inlet rings

for centrifugal fans

Fan size 280, Aluminium impeller

Part number


28070-2-4013




Fan size 310, RadiCal

Part number


31000-2-4013




Fan size 310, Aluminium impeller
Part number
31570-2-4013




Fan size 355, RadiCal
Part number
35500-2-4013



Fan size 400, Aluminium impeller
Part number
40070-2-4013





Technology

rail technology

ebmpapst

the engineer's choice

	Page
Connection diagrams	192
Technical parameters & scope	204

Connection diagram: BA1)

Technical features

- Control input 0-10 VDC / PWM
- Overvoltage detection
- Reverse polarity and locked-rotor protection
- Motor current limiter
- Tach output
- Soft start
- Over-temperature protected electronics

Wire 1




Wire	Designation	Colour	Assignment / function
1	UN +24 VDC	red	Power supply 24 VDC, residual ripple 3,5 %
	0-10 V / PWM	yellow	Control input: $R_i > 40 \text{ k}$ 0-10 V (Typ. $< 1 \text{ V} \rightarrow n=0$; $1,5 \text{ V} \rightarrow n=\text{min}$; $> 10 \text{ V} \rightarrow n=\text{max}$) PWM (Amplitude 10 V; 1-50 kHz; Typ. $< 5 \% \rightarrow n=0$; $15 \% \rightarrow n=\text{min}$; $100 \% \rightarrow n=\text{max}$)
	DUE	white	Speed monitoring output, Open Collector, 3 pulses per revolution, Isink max = 10 mA
	GND	blue	Reference Ground

Connection diagram: BA2)

Technical features

- Control input 0-10 VDC / PWM
- Output limit
- Reverse polarity and locked-rotor protection
- Motor current limiter
- Temperature derating
- Soft start
- Over-temperature protected electronics
- Diagnostic output
- Load Dump (58 V)
- Overvoltage detection

Wire 1



Wire	Designation	Colour	Assignment / function
1	UN +24 VDC	black	Power supply, voltage range see nameplate
	GND	brown	Power supply, voltage range see nameplate
	DIAG	white	Diagnostic output: Open Collector, Isink max = 10 mA, Ri > 2,1 kΩ fan ok -> high; fan error -> low
	0-10 V / PWM	yellow	Control input: Ri > 47 kΩ 0-10 V (Typ. < 1 V -> n=0; 1,5 V -> n=min; > 10 V -> n=max) PWM (Amplitude 10 V; 1-50 kHz; Typ. < 5 % -> n=0; 15 % -> n=min; 100 % -> n=max)

Connection diagram: BA3)

Technical features

- Control input 0-10 VDC / PWM
- Lowering input
- INVLIN (Control input invers linear)
- Fault output (Highside-Switch max. 10 mA)
- Temperature derating
- Output limit
- Reverse polarity and locked-rotor protection
- Soft start
- Over-temperature protected electronics
- Motor current limiter
- Overvoltage detection
- Load-Dump (58 V)

Wire 1



Wire	Designation	Colour	Assignment / function
1	UB +24 V DC	black	Power supply 24 V DC
	GND	brown	Power supply GND, reference ground
	0-10 V / PWM	yellow	Control input: $R_i > 47 \text{ k}\Omega$ 0-10 V (Typ. $< 1 \text{ V} \rightarrow n=0$; $1,5 \text{ V} \rightarrow n=\text{min}$; $> 10 \text{ V} \rightarrow n=\text{max}$) PWM (Amplitude 10 V; 1-50 kHz; Typ. $< 5 \% \rightarrow n=0$; $15 \% \rightarrow n=\text{min}$; $100 \% \rightarrow n=\text{max}$)
	INVLIN	orange	Control input invers linear ($U_b = \text{Standby}$, $21 \text{ V} = n \text{ min}$, $0 \text{ V} = n \text{ max}$)
	ABSENK	blue	Lowering input: when active ($>4 \text{ V}$) value of the control input is halved
	DU	white	Diagnostic output, Highside-switch, $I_{\text{sink}_{\text{max}}} = 10 \text{ mA}$, $R_i > 50 \Omega$ fan ok -> low; fan error -> high

Connection diagram: BA4)

Technical features

- Control input 0-10 VDC / PWM
- Fault output (Highside-Switch max. 10 mA)
- Temperature derating
- Output limit
- Reverse polarity and locked-rotor protection
- Soft start
- Over-temperature protected electronics
- Motor current limiter
- Overvoltage detection
- Load-Dump (58 V)

Wire 1




Wire	Designation	Colour	Assignment / function
1	UN +24 VDC	black	Power supply 24 VDC
	DIAG	white	Diagnostic output, Highside-switch, $I_{\text{sink,max}} = 10 \text{ mA}$, $R_i > 50 \Omega$ fan ok -> low; fan error -> high
	0-10 V / PWM	yellow	Control input: $R_i > 75 \text{ k}\Omega$ 0-10 V (Typ. $< 1 \text{ V} \rightarrow n=0$; $1,5 \text{ V} \rightarrow n=\text{min}$; $> 10 \text{ V} \rightarrow n=\text{max}$) PWM (Amplitude 10 V; 1-50 kHz; Typ. $< 5 \% \rightarrow n=0$; $15 \% \rightarrow n=\text{min}$; $100 \% \rightarrow n=\text{max}$)
	GND	brown	Power supply GND, reference ground

Connection diagram: BA5)

Technical features

- Control input 0-10 VDC / PWM
- Output 10 VDC, max. 10 mA
- Alarm relay
- Integrated PID controller
- Output limit
- Run monitoring
- Reverse polarity and locked-rotor protection
- Soft start
- Motor current limiter
- Overvoltage / Undervoltage detection
- RS485 MODBUS-RTU
- Maximum EEPROM write cycles 100.000
- Control interface with SELV potential safely disconnected from the mains
- Over-temperature protected electronics

Wire 1



Wire	Designation	Colour	Assignment / function
1	PE	green/yellow	Protective earth
	-	black	Power supply GND, voltage range see name plate
	+	brown	Power supply, voltage range see name plate
	COM	grey	Status relay, floating status contact, common connection, contact rating 250 VAC / max. 2 A (AC1) / min. 1 mA / 5 V, reinforced insulation according to EN 50124-1 for switching voltages up to 110 VDC
	NC	violet	Status relay, floating status contact, break for failure,, contact rating 250 VAC / max. 2 A (AC1) / min. 1 mA / 5 V, reinforced insulation according to EN 50124-1 for switching voltages up to 110 VDC
	0-10 V / PWM	yellow	Control input: $R_i = 100 \text{ k}\Omega$ 0-10 V (Typ. < 1 V -> n=0; 1,5 V -> n=min; > 10 V -> n=max) PWM (Amplitude 10 V; 1-50 kHz; Typ. < 5 % -> n=0; 15 % -> n=min; 100 % -> n=max) parametrisable curve, SELV
	RSB	orange	RS485 interface for MODBUS, RSB, SELV
	RSA	white	RS485 interface for MODBUS, RSA, SELV
	GND	blue	Signal ground for control interface, SELV
	+10 V	red	Fixed voltage output 10 VDC, +10 V +/- 3 %, max. 10 mA, short-circuit-proof, power supply for external devices (e.g. potentiometer), SELV

Connection diagram: BA6)

Technical features

- Control input 0-10 VDC / PWM
- Output 10 VDC, max. 10 mA
- Alarm relay
- Integrated PID controller
- Output limit
- Run monitoring
- Reverse polarity and locked-rotor protection
- Soft start
- Motor current limiter
- Overvoltage / Undervoltage detection
- RS485 MODBUS-RTU
- Maximum EEPROM write cycles 100.000
- Control interface with SELV potential safely disconnected from the mains
- Over-temperature protected electronics / Motor



Wire	Designation	Colour	Assignment / function
1	PE	green/yellow	Protective earth
	-	black	Power supply GND, voltage range see name plate
	+	brown	Power supply, voltage range see name plate
2	COM	grey	Status relay, floating status contact, common connection, contact rating 250 VAC / max. 2 A (AC1) / min. 1 mA / 5 V, reinforced insulation according to EN 50124-1 for switching voltages up to 110 VDC
	NC	orange	Status relay, floating status contact, break for failure,, contact rating 250 VAC / max. 2 A (AC1) / min. 1 mA / 5 V, reinforced insulation according to EN 50124-1 for switching voltages up to 110 VDC
	0-10 V / PWM	yellow	Control input: $R_i = 100 \text{ k}\Omega$ 0-10 V (Typ. < 1 V -> n=0; 1,5 V -> n=min; > 10 V -> n=max) PWM (Amplitude 10 V; 1-50 kHz; Typ. < 5 % -> n=0; 15 % -> n=min; 100 % -> n=max) parametrisable curve, SELV
	RSB	brown	RS485 interface for MODBUS, RSB, SELV
	RSA	white	RS485 interface for MODBUS, RSA, SELV
	GND	blue	Signal ground for control interface, SELV
	+10 V	red	Fixed voltage output 10 VDC, +10 V +/- 3 %, max. 10 mA, short-circuit-proof, power supply for external devices (e.g. potentiometer), SELV

Connection diagram: BA7)

Technical features

- Control input 0-10 VDC / PWM
- Output 10 VDC, max. 10 mA
- Alarm relay
- Integrated PID controller
- Undervoltage/phase failure detection
- Output limit / Run monitoring
- PFC (passive) / Soft start
- Over-temperature protected electronics / Motor
- Motor current limiter
- Overvoltage detection
- RS485 MODBUS-RTU
- Maximum EEPROM write cycles 100.000
- Control interface with SELV potential safely disconnected from the mains
- Locked-rotor protection




Wire	Designation	Colour	Assignment / function
1	PE	green/yellow	Protective earth
	L1	black	Power supply, Phase, 50/60 Hz
	L2	blue	Power supply, Phase, 50/60 Hz
	L3	brown	Power supply, Phase, 50/60 Hz
2	COM	grey	Status relay, floating status contact, common connection, contact rating 250 VAC / max. 2 A (AC1), min. 1 mA / 5 VDC, reinforced insulation on control interface side, basic insulation on supply side according to EN 50124-1
	NC	orange	Statusrelais, floating status contact, break for failure,, contact rating 250 VAC / max. 2 A (AC1), min. 1 mA / 5 VDC, reinforced insulation on control interface side, basic insulation on supply side according to EN 50124-1
	0-10 V / PWM	yellow	Control input: $R_i = 100 \text{ k}\Omega$ 0-10 V (Typ. < 1 V -> n=0; 1,5 V -> n=min; > 10 V -> n=max) PWM (Amplitude 10 V; 1-50 kHz; Typ. < 5 % -> n=0; 15 % -> n=min; 100 % -> n=max) parametrisable curve, SELV
	RSB	brown	RS485 interface for MODBUS, RSB, SELV
	RSA	white	RS485 interface for MODBUS, RSA, SELV
	GND	blue	Signal ground for control interface, SELV
	+10 V	red	Fixed voltage output 10 VDC, +10 V +/- 3 %, max. 10 mA, short-circuit-proof, power supply for external devices (e.g. potentiometer), SELV

Connection diagram: BA8)

Technical features

- Configurable inputs/outputs (I/O)
- RFID - ISO 15693 compatible
- Operation and alarm display with LED
- Integrated PID controller
- Reverse polarity and locked-rotor protection
- Motor current limiter / Alarm relay
- Soft start
- Undervoltage/phase failure detection
- Voltage output 3,3-24 VDC, Pmax = 800 mW
- RS 485 MODBUS-RTU / MODBUS V6
- Over-temperature protected electronics / Motor
- External 15-50 VDC input (parameterization)
- Control interface with SELV potential safely disconnected from supply




Terminal	Connection	Assignment / function
CON1	L1, L2, L3	Power supply, phase, voltage range see name plate, protection class 1
PE	PE	Protective earth
CON2	RSA	RS485 interface for MODBUS, RSA, SELV
	RSB	RS485 interface for MODBUS, RSB, SELV
	GND	Signal ground for control interface, SELV
	IO1	IN2: Digital input - positive logic (factory setting :Enable) funktion parameterizable, SELV - normal: Pin open or applied voltage < 1,5 VDC - invers: applied voltage 3,5-50 VDC
	IO2	IN1: Analog input 0-10 V 0-10 V, Ri=100 K, parameterizable as set value or measured value (factory setting: set value) parametrisable curve, SELV
	IO3	OUT1: Analog output 0-10 V 0-10 V, max 5 mA, funktion parameterizable (factory setting: modulation level)) max output frequency 300 Hz, SELV
	V out	Voltage output 3,3-24 VDC +/- 5 %, Pmax=800 mW, voltage parameterizable (factory setting: 10 VDC) short-circuitproof, supply for external devices, SELV alternatively: 15-50VDC input for parameterization via Modbus without line voltage
	COM	Status relay, floating status contact, common connection, nominal voltage 250VAC; max 2A (AC1), min 10mA; reinforced insulation according to EN60335-1, EN61800-5-1, UL60730-1
NC	Status relay, floating status contact, break for failure	

Connection diagram: BA9)

Technical features

- external TOP, basic insulation




Note: Change of rotation direction by reversing two phases

Δ	Delta connection
Y	Star connection
L1	black
L2	blue
L3	brown
U1	black
V1	blue
W1	brown
U2	green
V2	white
W2	yellow
TOP	2 x grey, contact rating 250 V AC
PE	green/yellow

Connection diagram: BA10)

Technical features

- Reverse polarity protection
- Control input 0-10 VDC / PWM / external temperature control module / resistance
- Locked-rotor protection (electrical restart)
- Tacho signal




Wire	Designation	Colour	Assignment / function
1	+ UB	red	Power supply
	GND	blue	Reference ground
	CONTR	violett	Multioptions control input
	Tacho	white	Tacho signal

Connection diagram: BA11)

Technical features

- Reverse polarity protection
- Control input 0-5VDC / PWM
- Locked-rotor protection (electrical restart)



Wire	Designation	Colour	Assignment / function
1	+ UB	red	Power supply
	GND	blue	Reference ground
	PWM	violett	Control input

Technical parameters & scope

High standards for all ebm-papst products

Here at ebm-papst, we constantly strive to further improve our products in order to be able to offer you the best possible product for your application. Careful monitoring of the market ensures that technical innovations are reflected in the improvements of our products. Based on the technical parameters listed below and the ambience you want our product to operate in, we here at ebm-papst can always work out the best solution for your specific application.

General performance parameters

Any deviations from the technical data and parameters described here are listed on the product-specific data sheet.

Degree of protection

The type of protection is specified in the product-specific data sheets.

Insulation class

The insulation class is specified in the product-specific data sheets.

Installation position

The mounting position is specified in the product-specific data sheets.

Condensate discharge holes

Information on the condensate discharge holes is provided in the product-specific data sheets.

Mode of operation

The mode of operation is specified in the product-specific data sheets.

Protection class

The protection class is specified in the product-specific data sheets.

Service life

The service life of ebm-papst automotive products depends:

– The service life of the bearing system

The service life of the insulation system mainly depends on voltage level, temperature and ambient conditions, such as humidity and condensation.

The service life of the bearing system depends mainly on the thermal load on the bearing.

The majority of our products use maintenance-free ball bearings for any mounting position possible.

The service life L10 of the ball bearings can be taken as approx. 40,000 operating hours at an ambient temperature of 40 °C, yet this estimate can vary according to the actual ambient conditions.

We will gladly provide you with a lifetime calculation taking into account your specific operating conditions.

Motor protection / thermal protection

Information on motor protection and thermal protection is provided in the product-specific data sheets.

Depending on motor type and field of application, the following protective features are realised:


- Thermal overload protector, connected
- PTC/NTC with electronic evaluation
- Current limiting using electronics

Mechanical strain / performance parameters

All ebm-papst products are subjected to comprehensive tests complying with the normative specifications. In addition to this, the tests also reflect the vast experience and expertise of ebm-papst.

High voltage and insulation testing

If high voltage or insulation testing is carried out in the application, then all connection lines from the fan must be disconnected in advance.



Balancing quality

Testing the balancing quality is carried out in compliance with

- Residual imbalance according to DIN ISO 1940
- Standard balancing quality level G 6.3

Should you require a higher balancing quality level for your specific application, please let us know and specify this when ordering your product.

Chemo-physical strain / performance parameters

Should you have questions about chemo-physical strain, please direct them to your ebm-papst contact.

Fields of application, industries and applications

Our products are used in various industries and applications:

The products in this catalogue have been specifically configured for use in the rail industry!

Legal and normative directives

The products described in this catalogue are designed, developed and produced in keeping with the standards in place for the relevant product and, if known, the conditions governing the relevant fields of application.

Standards

Information on standards is provided in the product-specific data sheets.

EMC

Information on EMC standards is provided in the product-specific data sheets. Complying with the EMC standards has to be established on the final appliance, as different mounting situations can result in changed EMC properties.

Approvals

In case you require a specific approval for your ebm-papst product (e1, UL, etc.) please let us know.

Most of our products can be supplied with the relevant approval. Information on existing approvals is provided in the product-specific data sheets.

Air performance measurements

All air performance measurements are carried out on suction side and on chamber test beds conforming to the specifications as per ISO 5801 and DIN 24163. The fans under test are installed in the measuring chamber at free air intake and exhaust (installation category A) and are operated at nominal voltage, with AC also at nominal frequency, and without any additional components such as guard grilles.

As required by the standard, the air performance curves correspond to an air density of 1.15 kg/m³.

Technical parameters & scope

Measurement conditions for air and noise measurement

ebm-papst products are measured under the following conditions:

- Axial and diagonal fans in direction of rotation "V" in full nozzle and without guard grill
- Backward curved centrifugal fans, free-running and with inlet nozzle
- Forward curved single and dual inlet centrifugal fans with housing

Noise measurements

All noise measurements are carried out in low-reflective test rooms with reverberant floor. Thus the ebm-papst acoustic test chambers meet the requirements of precision class 1 according to DIN EN ISO 3745. For noise measurement, the fans being tested are placed in a reverberant wall and operated at nominal voltage (for AC, also at nominal frequency) without additional attachments such as the guard grill.

Sound pressure level and sound level

All acoustic values are established according to ISO 13347, DIN 45635 and ISO 3744/3745 to accuracy class 2 and given in A-rated form.

When the sound pressure level (L_p) is measured, the microphone is on the intake side of the fan being tested, usually at a distance of 1 m on the fan axis.

To measure the sound power level (L_w) 10 microphones are distributed over an enveloping surface on the intake side of the fan being tested (see graphic). The sound power level measured can be roughly calculated from the sound pressure level by adding 7 dB.


Measuring configuration as per ISO 13347-3 bzw. DIN 45635-38:

- 10 measuring points

$$d \geq D$$

$$h = 1,5d \dots 4,5d$$

$$\text{Measurement area } S = 6d^2 + 7d(h + 1,5d)$$




Combined level of multiple same-level sound sources

Adding 2 noise sources with the same level results in a level increase of approx. 3 dB.

The noise characteristics of multiple identical fans can be determined in advance based on the noise values specified in the data sheet. This is shown in the diagram opposite.


Example: 8 A3G800 axial fans are on a condenser. According to the data sheet, the sound pressure level of a fan is approximately 75 dB(A). The level increase measured from the diagram is 9 dB. Thus the overall sound level of the installation can be expected to be 84 dB(A).



Combined level of two different-level sound sources


The acoustic performance of two different fans can be predetermined based on the sound levels given in the data sheet. This is shown in the diagram opposite.

Example: There is an axial fan A3G800 with a sound pressure level of 75 dB(A) at the operating point and an axial fan A3G710 with 71 dB(A) in a ventilation unit. The level difference is 4 dB. The level increase can now be read in the diagram as approx. 1.5 dB. This means that the overall sound level of the unit can be expected to be 76.5 dB(A).



Distance laws

Sound power level is independent of distance to the sound source. In contrast to this, sound pressure level decreases the further away the noise source is. The adjacent diagram shows the decrease in level under far sound field conditions. Far sound field conditions apply whenever the distance between microphone and fan is big when compared to fan diameter and wavelength to be considered. For more information on far sound field, please consult the relevant literature on this complex topic. Per doubling of distance, the level in the far sound field decreases by 6 dB. In the near field of the fan, other correlations apply and the decrease in levels can be considerably smaller. The following example only applies to far sound field conditions and can vary strongly depending on the installation effects: With an axial fan A3G300, a sound pressure level of 65 dB(A) was measured at a distance of 1 m. According to the adjacent diagram, at a distance of 20 m we would get a reduction by 26 dB, i.e. a sound pressure level of 39 dB(A).



Technology

Technical parameters & scope

Aerodynamics fundamentals:

Further information can be found in our brochure "Technology - Basic principles"

Axial fan operating range:

To the right of the saddle point (right section of the air performance curve):

- Maximum efficiency
- Minimum noise

To the left of the saddle point (left section of the air performance curve):

- Stall
- Irruptive efficiency
- Noise suddenly increases

The fan's optimal range of use is highlighted in green in the adjoining performance curve.


Effects of guard grill:

Installing a guard grill reduces the axial fan's air performance.

The pressure loss in Pa can be roughly calculated using the following equation:

$$\Delta p_{SG} = \epsilon_{SG} \cdot 10^{-8} \cdot \dot{V}^2 \quad \dot{V} \text{ in } [m^3/h]$$

For the guard grill that ebm-papst used, the correction factor ϵ_{SG} dependent on impeller diameter D can be found in the adjoining table.



Diameter D	Correction factor ϵ_{SG}
400	90
450	55
500	35

Centrifugal fan operating range:


Middle section of the air performance curve:

- Maximum efficiency
- Minimum noise

To the left and right of the middle section of the air performance curve:


- Reduced efficiency
- Increasing noise

The fan's optimal range of use is highlighted in green in the adjoining performance curve.




Effects of installation space

Installation in a square box may cause a reduction of the air performance.



- d_h = hydraulic diameter
Formula: $d_h = 2 \times W \times H / (W + H)$
- W = Width of the box
- H = Height of the box
- D = Outside diameter of the fan



Airflow determination for inlet rings with pressure tap:

The differential pressure method compares the static pressure upstream of the inlet ring with the static pressure in the inlet ring. The airflow can be calculated from the differential pressure (between the static pressures) according to the following equation:


$$q_v = k \cdot \sqrt{\Delta p} \quad q_v \text{ in [m}^3/\text{h] and } \Delta p \text{ in [Pa]}$$

If the airflow is to be regulated to remain constant, the inlet pressure must be kept constant:

$$\Delta p = q_v^2 : k^2$$

k takes the specific properties of the inlet ring into account.

The pressure is tapped at 1 (4) point(s) on the circumference of the inlet ring. The customer connection consists of a built-in T-shaped hose fitting. The hose fitting is suitable for pneumatic hoses with an inside diameter of 4 mm.




Influence of speed n on the sound power level Lw:

The sound power level for changes in speed can be approximately determined based on the adjoining diagram and the following formula:

$$Lw_2 - Lw_1 = 50 \text{ dB} \cdot \log(n_2 : n_1)$$

- Lw_1 = Sound power level after speed change
- Lw_2 = Sound power level before speed change
- n_1 = Changed speed
- n_2 = Initial speed



ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2
74673 Mulfingen
GERMANY
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com

ebm-papst St. Georgen GmbH & Co. KG

Hermann-Papst-Straße 1
78112 St. Georgen
GERMANY
Phone +49 7724 81-0
Fax +49 7724 81-1309
info2@de.ebmpapst.com

ebm-papst Landshut GmbH

Hofmark-Aich-Straße 25
84030 Landshut
GERMANY
Phone +49 871 707-0
Fax +49 871 707-465
info3@de.ebmpapst.com



Agents

Worldwide

ebmpapst

the engineer's choice

	Page
ebm-papst in Germany	212
ebm-papst in Europe	213
ebm-papst in America and Africa	215
ebm-papst in Asia	216
ebm-papst in Oceania	217

ebm-papst in Germany



Berlin
Dipl.-Ing. (TH) Jens Duchow
Händelstraße 7
16341 Panketal
GERMANY
Phone +49 30 944149-62
Fax +49 30 944149-63
Jens.Duchow@de.ebmpapst.com



Bielefeld
Dipl.-Ing. (FH) Wolf-Jürgen Weber
Niehausweg 13
33739 Bielefeld
GERMANY
Phone +49 5206 91732-31
Fax +49 5206 91732-35
Wolf-Juergen.Weber@de.ebmpapst.com



Dortmund
Dipl.-Ing. (FH) Hans-Joachim Pundt
Auf den Steinern 3
59519 Möhnensee-Völlinghausen
GERMANY
Phone +49 2925 800-407
Fax +49 2925 800-408
Hans-Joachim.Pundt@de.ebmpapst.com



Frankfurt
Dipl.-Ing. Christian Kleffmann
Dr.-Hermann-Krause-Straße 23
63452 Hanau
GERMANY
Phone +49 6181 1898-12
Fax +49 6181 1898-13
Christian.Kleffmann@de.ebmpapst.com



Halle
Dipl.-Ing. (TU) Michael Hanning
Lercheneck 4
06198 Salztal / OT Lieskau
GERMANY
Phone +49 345 55124-56
Fax +49 345 55124-57
Michael.Hanning@de.ebmpapst.com



Hamburg
Ingenieurbüro Breuell GmbH
Ing. Dirk Kahl
Elektroingenieur
Oststraße 96
22844 Norderstedt
GERMANY
Phone +49 40 538092-19
Fax +49 40 538092-84
Kahl@breuell-hilgenfeldt.de



Heilbronn / Heidelberg
Wolfgang Richter
Büttelsbergweg 18
97980 Bad Mergentheim-Rengershausen
GERMANY
Phone +49 7937 32200-33
Fax +49 7938 81-110
Wolfgang.Richter@de.ebmpapst.com



Kassel
Dipl.-Ing. (FH) Ralph Brück
Hoherainstraße 3 b
35075 Gladenbach
GERMANY
Phone +49 6462 4071-10
Fax +49 6462 4071-11
Ralph.Brueck@de.ebmpapst.com



Koblenz
Winfried Schaefer
Hinter der Kirch 10
56767 Uersfeld
GERMANY
Phone +49 2657 16-96
Fax +49 2657 16-76
Winfried.Schaefer@de.ebmpapst.com



Munich
Dipl.-Wirt.-Ing. (FH) Jens Peter
Landsbergerstraße 14
86932 Pürgen
GERMANY
Phone +49 8196 99877-54
Fax +49 8196 99877-55
Jens.Peter@de.ebmpapst.com



Nuremberg
Dipl.-Wirt.-Ing. (FH) Axel Resch
Dr.-August-Koch-Str. 1
91639 Wolframs-Eschenbach
GERMANY
Phone +49 9875 9783-170
Fax +49 9875 9783-171
Axel.Resch@de.ebmpapst.com



Offenburg
Dipl.-Ing. (FH) Ralf Braun
Hubeneck 21
77704 Oberkirch
GERMANY
Phone +49 7802 9822-52
Fax +49 7802 9822-53
Ralf.Braun@de.ebmpapst.com



Stuttgart
Dipl.-Ing. (FH) Rudi Weinmann
Hindenburgstraße 100/1
73207 Plochingen
GERMANY
Phone +49 7153 9289-80
Fax +49 7153 9289-81
Rudi.Weinmann@de.ebmpapst.com



Ulm
M.Sc. Reinhard Sommerreißer
Einsteinstraße 7a
86674 Baar / Schwaben
GERMANY
Phone +49 8276 5899-775
Fax +49 7938 81-110
Reinhard.Sommerreisser@de.ebmpapst.com

Distributors



Frankfurt
R.E.D. Handelsgesellschaft mbH
Gutenbergstraße 3
63110 Rodgau - Jügesheim
GERMANY
Phone +49 6106 841-0
Fax +49 6106 841-111
info@red-elektromechnik.de
www.red-elektromechnik.de



Hamburg
Breuell + Hilgenfeldt GmbH
Oststraße 96
22844 Norderstedt
GERMANY
Phone +49 40 538092-20
Fax +49 40 538092-84
info@breuell-hilgenfeldt.de



Munich
A. Schweiger GmbH
Ohmstraße 1
82054 Sauerlach
GERMANY
Phone +49 8104 897-0
Fax +49 8104 897-90
info@schweiger-gmbh.de
www.schweiger-gmbh.com


● **Express Service-Center** (1 to 5 pieces)




North
Breuell + Hilgenfeldt GmbH
Oststraße 96
22844 Norderstedt
GERMANY
Phone +49 40 538092-20
Fax +49 40 538092-84
info@breuell-hilgenfeldt.de




South
HDS Ventilatoren Vertriebs GmbH
Glaswiesenstraße 1
74677 Dörzbach
GERMANY
Phone +49 7937 80355-20
Fax +49 7937 80355-25
info@hds-gmbh.net
www.hds-gmbh.net



fan agent



compact fan agent



motor specialist






motor agent



ebm-papst in Europe


Europe

 **Austria**
ebm-papst Motoren & Ventilatoren GmbH
 Straubingstraße 17
 4030 Linz
AUSTRIA
Phone +43 732 321150-0
Fax +43 732 321150-20
info@at.ebmpapst.com
www.ebmpapst.at

 **Belarus**
ebm-papst Bel AgmbH
 4th Montazhnikov side street
 House 6, Office 332
BY-220019 Minsk
BELARUS
Phone +375 17 2015216
Fax +375 17 2015216
info@by.ebmpapst.com
www.ebmpapst.by

 **Belgium**
ebm-papst Benelux B.V.
 Sales office Belgium-Luxemburg
 Romeinsestraat 6/0101
Research Park Haasrode
3001 Heverlee-Leuven
BELGIUM
Phone +32 16 396-200
Fax +32 16 396-220
info@be.ebmpapst.com
www.ebmpapst.be

 **Bulgaria**
ebm-papst Romania S.R.L.
 Str. Tarnavei No. 20
 500327 Brasov
ROMANIA
Phone +40 268 331859
Fax +40 268 312805
dudasludovic@xnet.ro

 **Croatia**
ebm-papst Industries Kft.
 Ezred u. 2.
 1044 Budapest
HUNGARY
Phone +36 1 8722-190
Fax +36 1 8722-194
office@hu.ebmpapst.com

 **Cyprus**
Helcoma
 E. Rota and Co. OE
 Davaki 65
17672 Kallithea-Attiki
GREECE
Phone +30 210 9513-705
Fax +30 210 9513-490
contact@helcoma.gr
www.helcoma.gr

 **Czech Republic / Slovakia**
ebm-papst CZ s.r.o.
 Kaštanová 34a
 620 00 Brno
CZECH REPUBLIC
Phone +420 544 502-411
Fax +420 547 232-622
info@ebmpapst.cz
www.ebmpapst.cz




 **Denmark**
ebm-papst Denmark ApS
 Vallensbækvej 21
 2605 Brøndby
DENMARK
Phone +45 43 631111
Fax +45 43 630505
mail@dk.ebmpapst.com
www.ebmpapst.dk

 **Estonia**
ebm-papst Oy, Eesti Filiaal
 Kesk tee 21
 Aaviku küla, Jüri Tehnopark
75301 Rae Vald, Harjumaa
ESTONIA
Phone +372 65569-78
www.ebmpapst.ee


 **Finland**
ebm-papst Oy
 Puistotie 1
 02760 Espoo
FINLAND
Phone +358 9 887022-0
Fax +358 9 887022-13
mailbox@ebmpapst.fi
www.ebmpapst.fi



 **France**
ebm-papst sarl
 Parc d'Activités Nord
 1 rue Mohler – BP 62
67212 Obernai Cedex
FRANCE
Phone +33 3 88 66 88 03
info@ebmpapst.fr
www.ebmpapst.fr

 **Greece**
HELCOMA
 HELLAS IKE
 65, Davaki street
17672 Kallithea-Attiki
GREECE
Phone +30 210 9513-705
Fax +30 210 9513-490
contact@helcoma.gr
www.helcoma.gr


 **Hungary**
ebm-papst Industries Kft.
 Ezred u. 2.
 1044 Budapest
HUNGARY
Phone +36 1 8722-190
Fax +36 1 8722-194
office@hu.ebmpapst.com

 **Iceland**
RJ Engineers
 Stangarhyl 1a
 110 Reykjavik
ICELAND
Phone +354 567 8030
Fax +354 567 8015
rj@rj.is
www.rj.is


 **Ireland**
ebm-papst UK Ltd.
 Chelmsford Business Park
 Chelmsford Essex CM2 5EZ
UNITED KINGDOM
Phone +44 1245 468555
Fax +44 1245 466336
sales@uk.ebmpapst.com
www.ebmpapst.co.uk

 AuBren Limited
 Portlaoise Business & Technology Park
 Mountrath Road
Portlaoise, Co. Laois
IRELAND
Phone +353 57 8664343
Fax +353 57 8664346
sales@ie.aubren.com
www.aubren.com


 **Italy**
ebm-papst Srl
 Via Cornaggia 108
 22076 Mozzate (Co)
ITALY
Phone +39 0331 836201
Fax +39 0331 821510
info@it.ebmpapst.com
www.ebmpapst.it




fan agent



compact fan agent



motor specialist



motor agent

ebm-papst in Europe



Macedonia

ebm-papst Industries Kft.
Ezred u. 2.
1044 Budapest
HUNGARY
Phone +36 1 8722-190
Fax +36 1 8722-194
office@hu.ebmpapst.com



Netherlands

ebm-papst Benelux B.V.
Polbeemd 7 - 5741 TP Beek en Donk
P.O. Box 140 - 5740 AC Beek en Donk
NETHERLANDS
Phone +31 492 502-900
Fax +31 492 502-950
verkoop@nl.ebmpapst.com
www.ebmpapst.nl

ebm-papst Heating Systems B.V.
Van Veldekekade 360
5216 KT 's-Hertogenbosch
NETHERLANDS
Phone +31 73 648 89 00
Fax +31 73 648 89 11
info@ebmpapst-hs.nl
www.ebmpapst-hs.nl



Norway

ebm-papst AS
P.B. 173 Holmlia
1203 Oslo
NORWAY
Phone +47 22 763340
Fax +47 22 619173
mailbox@ebmpapst.no
www.ebmpapst.no



Poland

ebm-papst Polska Sp. z o.o.
ul. Annopol 4A
03236 Warszawa
POLAND
Phone +48 22 6757819
Fax +48 22 6769587
office@ebmpapst.pl
www.ebmpapst.pl



Portugal

ebm-papst (Portugal), Lda.
Centro Empresarial de Alverca
Rua de Adarse, Vale D'Ervas
Corpo D / Fracção 3
2615-178 Alverca do Ribatejo
PORTUGAL
Phone +351 218 394 880
Fax +351 218 394 759
info@pt.ebmpapst.com
www.ebmpapst.pt



Romania

ebm-papst Romania S.R.L.
Str. Tarnavei Nr. 20
500327 Brasov
ROMANIA
Phone +40 268 331859
Fax +40 268 312805
dudasludovic@xnet.ro



Russia

ebm-papst Rus GmbH
Olimpiyskiy prospect 29A, office 418
141006 Mytistschi, Oblast Moskau
RUSSIA
Phone +7 495 9807524
Fax +7 495 5140924
info@ebmpapst.ru
www.ebmpapst.ru



ebm-papst Ural GmbH
Posadskaja-Strasse, 23(E), 3
620102 Ekaterinburg
RUSSIA

Phone +7 343 2338000
Fax +7 343 2337788
Konstantin.Molokov@ru.ebmpapst.com
www.ebmpapst.us



Serbia & Montenegro

ebm-papst Industries Kft.
Ezred u. 2.
1044 Budapest
HUNGARY
Phone +36 1 8722-190
Fax +36 1 8722-194
office@hu.ebmpapst.com



Spain

ebm-papst Ibérica S.L.
Avda. del Sistema Solar, 29
28830 San Fernando de Henares (Madrid)
SPAIN
Phone +34 91 6780894
Fax +34 91 6781530
ventas@ebmpapst.es
www.ebmpapst.es



Sweden

ebm-papst AB
Aggelundavägen 2
17562 Järfälla
SWEDEN
Phone +46 10 4544400
Fax +46 8 362306
info@ebmpapst.se
www.ebmpapst.se



Switzerland

ebm-papst AG
Rütisbergstrasse 1
8156 Oberhasli
SWITZERLAND
Phone +41 44 73220-70
Fax +41 44 73220-77
verkauf@ebmpapst.ch
www.ebmpapst.ch



Turkey

Akantel Elektronik San. Tic. LTD. Sti.
Atatürk Organize Sanayi
Bölgesi 10007 SK. No.:6
35620 Cigli-Izmir
TURKEY
Phone +90 232 3282090
Fax +90 232 3280270
akantel@akantel.com.tr
www.ebmpapst.com.tr



Ukraine

ebm-papst Ukraine LLC
Lepse Boulevard, 4, Building 21
03067 Kiev
UKRAINE
Phone +38 044 2063091
Fax +38 044 2063091
mail@ebmpapst.ua
www.ebmpapst.ua




United Kingdom

ebm-papst UK Ltd.
Chelmsford Business Park
Chelmsford Essex CM2 5EZ
UNITED KINGDOM
Phone +44 1245 468555
Fax +44 1245 466336
sales@uk.ebmpapst.com
www.ebmpapst.co.uk




ebm-papst Automotive & Drives (UK) Ltd.


The Smithy
Fidlers Lane
East Ilsley, Berkshire RG20 7LG
UNITED KINGDOM
Phone +44 1635 2811-11
Fax +44 1635 2811-61
A&Dsales@uk.ebmpapst.com
www.ebmpapst-ad.com




fan agent



compact fan agent



motor specialist



motor agent

ebm-papst in America & Africa

America



Argentina

ebm-papst Argentina S.A.
Parque Industrial Canning Etapa II - Nave
61A, Perito Moreno 845, Canning (1804),
Buenos Aires
ARGENTINA
Phone +54 11 46576135
Fax +54 11 46572092
ventas@ar.ebmpapst.com
www.ebmpapst.com.ar



Brazil

ebm-papst Motores Ventiladores Ltda.
Av. José Giorgi, 301 Galpões B6+B7
Condominio Logical Center
06707-100 Cotia - São Paulo
BRAZIL
Phone +55 11 4613-8700
Fax +55 11 4777-1456
vendas@br.ebmpapst.com
www.ebmpapst.com.br



Canada

ebm-papst Canada Inc.
1800 Ironstone Manor, Unit 2
Pickering, Ontario, L1W3J9
CANADA
Phone +1 905 420-3533
Fax +1 905 420-3772
sales@ca.ebmpapst.com
www.ebmpapst.ca



Mexico

ebm Industrial S. de R.L. de C.V.
Paseo de Tamarindos 400-A-5to Piso
Col. Bosques de las Lomas
Mexico 05120, D.F.
MEXICO
Phone +52 55 3300-5144
Fax +52 55 3300-5243
sales@mx.ebmpapst.com
www.ebmpapst.com.mx

USA



ebm-papst Inc.
P.O. Box 4009
100 Hyde Road
Farmington, CT 06034
UNITED STATES
Phone +1 860 674-1515
Fax +1 860 674-8536
sales@us.ebmpapst.com
www.ebmpapst.us




ebm-papst Inc.
Automotive & Drives Business Unit
3200 Greenfield Road, Suite 130
Dearborn, MI 48120
UNITED STATES
Phone +1 313 406-8080
Fax +1 313 406-8081
automotive@us.ebmpapst.com
www.ebmpapst-automotive.us

Africa



South Africa

ebm-papst South Africa (Pty) Ltd.
P.O. Box 3124
1119 Yacht Avenue
2040 Honeydew
SOUTH AFRICA
Phone +27 11 794-3434
Fax +27 11 794-5020
info@za.ebmpapst.com
www.ebmpapst.co.za



fan agent



compact fan agent



motor specialist



motor agent

ebm-papst in Asia

Asia



China

ebm-papst Ventilator (Shanghai) Co., Ltd.
No. 418, Huajing Road
WaiGaoQiao Free Trade Zone
No. 2001, Yang Gao (N) Road
200131 Shanghai
P.R. of CHINA
Phone +86 21 5046-0183
Fax +86 21 5046-1119
sales@cn.ebmpapst.com
www.ebmpapst.com.cn



Hong Kong

ebm-papst Hong Kong Ltd.
Room 17E, MG Tower
133 Hoi Bun Road, Kwun Tong
Hong Kong
P.R. of CHINA
Phone +852 2145-8678
Fax +852 2145-7678
info@hk.ebmpapst.com



India

ebm-papst India Pvt. Ltd.
26/3, G.N.T. Road, Erukkencherry
Chennai-600118
INDIA
Phone +91 44 25372556
Fax +91 44 25371149
sales@in.ebmpapst.com
www.ebmpapst.in



Indonesia

ebm-papst Indonesia
Representative Office
German Centre, 4th Floor, Suite 4470
Jl. Kapt. Subijono Dj. Bumi Serpong Damai
15321 Tangerang
INDONESIA
Phone +62 21 5376250
Fax +62 21 5388305
salesdept@id.ebmpapst.com



Israel

Polak Bros. Import Agencies Ltd.
9 Hamefalsim Street
Kiryat Arie, Petach-Tikva 49514
ISRAEL
Phone +972 3 9100300
Fax +972 3 5796679
polak@polak.co.il
www.polak.co.il



Japan

ebm-papst Japan K.K.
Attend on Tower 13F
Shinyokohama 2-8-12, Kohoku-ku
222-0033 Yokohama-City, Kanagawa
JAPAN
Phone +81 45 47057-51
Fax +81 45 47057-52
info@jp.ebmpapst.com
www.ebmpapst.jp



Korea

ebm-papst Korea Co. Ltd.
6F, Trutec Bldg.
12, WorldCupbuk-ro 56-gil
Mapo-Gu
Seoul 03924
KOREA
Phone +82 2 366213-24
Fax +82 2 366213-26
info@kr.ebmpapst.com
www.ebmpapst.co.kr



Malaysia

ebm-papst Malaysia
Representative Office
No. 16-1, Jalan Putra Mahkota 7/5A
Putra Heights
Selangor Darul Ehsan
47650 Subang Jaya
MALAYSIA
Phone +60 3 5192-7688
Fax +60 3 5614-3078
salesdept@my.ebmpapst.com



Philippines

ebm-papst SEA Pte. Ltd.
Representative Office (Philippines)
ALPAP II Building
Trade Street Corner Investment Drive
Unit 1101 Madrigal Business Park
1799 Ayala Alabang / Muntinlupa City
Telefon: +63 02 8042747
Telefax: +63 02 8042757
salesdept@ph.ebmpapst.com



Singapore

ebm-papst SEA Pte. Ltd.
9 Tai Seng Drive
#03-01 Geo-Tele Centre, Lobby B
Singapore 535227
SINGAPORE
Phone +65 65513789
Fax +65 68428439
salesdept@sg.ebmpapst.com



Taiwan

ETECO Engineering & Trading Corp.
10F-I, No. 92, Teh-Wei Str.
Tsow-Inn District, Kaohsiung
TAIWAN
Phone +886 7 557-4268
Fax +886 7 557-2788
eteco@ms22.hinet.net
www.ebmpapst.com.tw



Thailand

ebm-papst Thailand Co., Ltd.
99/9 Moo 2, Central Chaengwattana Tower
14th Floor, Room 1402
Chaengwattana Road Bangtarad, Pakkret
11120 Nonthaburi
THAILAND
Phone +66 2 8353785-7
Fax +66 2 8353788
salesdept@th.ebmpapst.com




United Arab Emirates

ebm-papst Middle East FZE
PO Box 17755
Jebel Ali Free Zone / FZS1 / AP05
Dubai
UNITED ARAB EMIRATES
Phone +971 4 88608-26
Fax +971 4 88608-27
info@ae.ebmpapst.com
www.ebmpapst.ae




Vietnam


ebm-papst SEA Pte. Ltd.
Representative Office (Vietnam)
Floor M, Phuong Long Building,
506 Nguyen Dinh Chieu Street,
Ward 4, District 3,
Ho Chi Minh City, Vietnam
VIETNAM
Phone +84 28 3929 0699 / 3929 0670
Fax +84 28 3929 0669
salesdept@vn.ebmpapst.com




fan agent



compact fan agent



motor specialist





motor agent

ebm-papst in Oceania

Oceania

 **Australia**
ebm-papst A&NZ Pty Ltd.
 10 Oxford Road
 Laverton North, Victoria, 3026
AUSTRALIA
Phone +61 3 9360-6400
Fax +61 3 9360-6464
sales@ebmpapst.com.au
www.ebmpapst.com.au

 **New Zealand**
ebm-papst A&NZ Pty Ltd.
 61 Hugo Johnston Drive, Unit H
 Penrose 1061, Auckland
NEW ZEALAND
PO Box 112278,
Penrose 1642, Auckland
Phone +64 9 525-0245
Fax +64 9 525-0246
sales@ebmpapst.com.au
www.ebmpapst.com.au



Notes

Notes

ebmpapst

the engineer's choice



ebm-papst
Mulfingen GmbH & Co. KG

Bachmühle 2
74673 Mulfingen
Germany
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com

ebm-papst
St. Georgen GmbH & Co. KG

Hermann-Papst-Straße 1
78112 St. Georgen
Germany
Phone +49 7724 81-0
Fax +49 7724 81-1309
info2@de.ebmpapst.com